

# SAFETY DATA SHEET

Published DateRevision DateRevision NumberJan-03-2024Jan-03-20242.6

# 1. IDENTIFICATION

**Product identifier** 

Product code 97LF18
Product name Scarlet Red

Product category 9700 Series SV Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Industrial Printing Operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Barton Road
Heaton Mersey

Tel: +001-913-422-1888 Stockport, England SK4 3EG Tel: +001-800-677-4657 Tel: +44 161 442 2111

Fax: +001-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: +001-800-424-9300

Outside USA: Chemtrec: +001-703-527-3887

24 Hour Emergency Phone Number

# 2. HAZARDS IDENTIFICATION

### Classification

| Acute toxicity - Inhalation (Vapors)      | Category 3 - (H331) |
|---|---------------------|
| Acute toxicity - Inhalation (Dusts/Mists) | Category 3 - (H331) |
| Skin corrosion/irritation                 | Category 2 - (H315) |
| Serious eye damage/eye irritation         | Category 2 - (H319) |
| Skin sensitization                        | Category 1 - (H317) |

### Label elements



Signal word Danger

# **Hazard statements**

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H331 - Toxic if inhaled

#### **Precautionary Statements**

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P280 - Wear protective gloves and eye/face protection

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P311 - Call a POISON CENTER or doctor

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

### Hazards not otherwise classified (HNOC)

No information available.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

| Chemical name   | CAS No.       | Weight-% | Trade<br>secret | Note |
|-----------------|---------------|----------|-----------------|------|
| 2-Butoxyethanol | 111-76-2      | 30 - 60  | *               |      |
| Resin           | Not Available | 5 - 10   | *               |      |

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST-AID MEASURES

### Description of first aid measures

**General Advice** Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

**Skin Contact** Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

**Inhalation** Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

### Most important symptoms and effects, both acute and delayed

None under normal use conditions.

### Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

# Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Unsuitable Extinguishing Media

No information available.

#### **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

# 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

### **Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

# Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

**Handling**Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

### Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open

flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep

out of the reach of children.

**Incompatible Products** Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

### **Exposure limits**

| Chemical name   | ACGIH TLV   |
|-----------------|-------------|
| 2-Butoxyethanol | TWA: 20 ppm |
| 111-76-2        |             |
|                 |             |
| Chemical name   | OSHA PEL    |

| Chemical name   | OSHA PEL                   |
|-----------------|----------------------------|
| 2-Butoxyethanol | TWA: 50 ppm                |
| 111-76-2        | TWA: 240 mg/m <sup>3</sup> |
|                 | Skin                       |

| Chemical name   | OSHA PEL (vacated)         |
|-----------------|----------------------------|
| 2-Butoxyethanol | TWA: 25 ppm                |
| 111-76-2        | TWA: 120 mg/m <sup>3</sup> |
|                 | Skin                       |

| Chemical name   | Ontario TWAEV |
|-----------------|---------------|
| 2-Butoxyethanol | TWA: 20 ppm   |
| 111-76-2        |               |

| Chemical name   | Mexico OEL (TWA)    |
|-----------------|---------------------|
| 2-Butoxyethanol | TWA/VLE-PPT: 20 ppm |

| 111-76-2 |  |
|----------|--|
|          |  |

#### Appropriate engineering controls

**Engineering Measures** Provide a good standard of general ventilation. Natural ventilation is from doors, windows

etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In

case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear **Eye/Face Protection** 

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

**Skin Protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as

appropriate, to prevent skin contact.

**Hand Protection** Chemical resistant protective gloves.

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6,

corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene

rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a

chemical-protective glove in practice may be much shorter than the permeation time

determined through testing.

Due to different glove types, the manufacturer's directions for use should be observed.

Replace gloves immediately when torn or any change in appearance is noticed such as

dimension, color, flexibility.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved **Respiratory Protection** 

respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of

the material.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

**Physical state** Liquid **Appearance** Colored

Odor Characteristic **Odor Threshold** No information available

Remarks • Method **Property** Values Hq No data available **Melting Point / Freezing Point** No information available No data available

**Boiling Point / Boiling Range** > 149 °C / 300 °F

Flash Point 62 °C / 143 °F Pensky Martens Closed Cup (PMCC)

**Evaporation rate** No data available

Flammability Limit in Air Upper flammability limit No data available Lower flammability limit No data available **Vapor Pressure** No data available

**Vapor Density** No data available **Specific Gravity** 1

Water Solubility No data available

Solubility in other solvents
Partition coefficient: n-octanol/water

Autoignition Temperature Hyphen

No information available

No data available No data available No data available No data available

No data available

No data available

Kinematic viscosity Dynamic viscosity

**Explosive Properties** 

**Oxidizing Properties** 

No data available No data available

Other information

Photochemically Reactive No Weight Per Gallon (lbs/gal) 8.34

| VOC by weight % | VOC by volume % | VOC lbs/gal  | VOC grams/liter |  |
|-----------------|-----------------|--------------|-----------------|--|
| (less water)    | (less water)    | (less water) | (less water)    |  |
| 57.32           | 59.11           | 4.78         | 573.25          |  |

# 10. STABILITY AND REACTIVITY

### Reactivity

No information available.

### Chemical stability

Stable under normal conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

### Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Inhalation** Specific test data for the substance or mixture is not available. Toxic if inhaled. (based on

components).

Eye ContactSpecific test data for the substance or mixture is not available.Skin ContactSpecific test data for the substance or mixture is not available.IngestionSpecific test data for the substance or mixture is not available.

| Chemical name   | Oral LD50         |
|-----------------|-------------------|
| 2-Butoxyethanol | = 470 mg/kg (Rat) |
| 111-76-2        |                   |

| Chemical name   | Dermal LD50            |
|-----------------|------------------------|
| 2-Butoxyethanol | = 435 mg/kg ( Rabbit ) |
| 111-76-2        |                        |
| Resin           | > 2000 mg/kg (Rat)     |
|                 |                        |

| Chemical name | Inhalation LC50 |
|---------------|-----------------|
|               |                 |

| 2-Butoxyethanol | = 450 ppm (Rat) 4 h |
|-----------------|---------------------|
| 111-76-2        | = 486 ppm (Rat) 4 h |

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Specific test data for the substance or mixture is not available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**Specific test data for the substance or mixture is not available. Causes skin irritation (pain,

redness and swelling). (based on components).

**Eye damage/irritation** Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components).

IrritationSpecific test data for the substance or mixture is not available.CorrosivitySpecific test data for the substance or mixture is not available.

Sensitization Specific test data for the substance or mixture is not available. May cause an allergic skin

reaction. (based on components).

Mutagenic EffectsSpecific test data for the substance or mixture is not available.Carcinogenic effectsSpecific test data for the substance or mixture is not available.Reproductive EffectsSpecific test data for the substance or mixture is not available.STOT - single exposureSpecific test data for the substance or mixture is not available.STOT - repeated exposureSpecific test data for the substance or mixture is not available.Chronic ToxicitySpecific test data for the substance or mixture is not available.Aspiration hazardSpecific test data for the substance or mixture is not available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

| Carcinogenicity | The table below indicates whether each agency has listed any ingredient as a carcinogen. |       |
|-----------------|--|-------|
| Chemical name   |  | ACGIH |
| 2-Butoxyethanol |  | A3    |
| 111-76-2        |  |       |

# Numerical measures of toxicity - Product Information

**Unknown acute toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 821.40 mg/kg
ATEmix (dermal) 99,999.00 mg/kg
ATEmix (inhalation-gas) 99,999.00
ATEmix (inhalation-dust/mist) 0.876 mg/l
ATEmix (inhalation-vapor) 5.24 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Specific test data for the substance or mixture is not available.

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

| Chemical name   | Fish   |
|-----------------|--|
| 2-Butoxyethanol | 96h LC50 Lepomis macrochirus: = 1490 mg/L (static) |
| 111-76-2        | 96h LC50 Lepomis macrochirus: = 2950 mg/L          |
| Resin           | 96h LC50 Oncorhynchus mykiss: = 11.5 mg/L (static) |
|                 |  |

| Chemical name   | Crustacea                           |
|-----------------|-------------------------------------|
| 2-Butoxyethanol | 48h EC50 Daphnia magna: > 1000 mg/L |

111-76-2

#### **Persistence and Degradability**

No information available.

#### **Bioaccumulation**

| Chemical name   | Partition coefficient |
|-----------------|-----------------------|
| 2-Butoxyethanol | 0.81                  |
| 111-76-2        |                       |

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. TRANSPORT INFORMATION

**Note:** This information is not intended to convey all specific transportation requirements relating to

this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and

rules relating to the transportation of the material.

DOT

UN/ID no UN2810

Proper Shipping Name Toxic Liquid, Organic, N.O.S. (2-Butoxyethanol)

Transport hazard class(es) 6.1
Packing Group III

ICAO / IATA / IMDG / IMO

UN/ID no UN2810

Proper Shipping Name Toxic Liquid, Organic, N.O.S. (2-Butoxyethanol)

Transport hazard class(es) 6.1
Packing Group

# 15. REGULATORY INFORMATION

# **International Inventories**

All substances are listed as ACTIVE on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

# **U.S. Federal Regulations**

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Chemical name   | CAS No.  | Weight-% | SARA 313 - Threshold<br>Values % |
|-----------------|----------|----------|----------------------------------|
| 2-Butoxyethanol | 111-76-2 | 30 - 60  | 1.0                              |

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

### **US State Regulations**

| Chemical name               | Massachusetts              |  |
|-----------------------------|----------------------------|--|
| 2-Butoxyethanol             | Х                          |  |
| 111-76-2                    |                            |  |
| Chemical name               | Minnesota<br>Right To Know |  |
| 2-Butoxyethanol<br>111-76-2 | X                          |  |
| Chemical name               | New Jersey                 |  |
| 2-Butoxyethanol             | X                          |  |
| 111-76-2                    |                            |  |
| Chemical name               | Pennsylvania               |  |
| 2-Butoxyethanol             | X                          |  |

# **California Proposition 65**

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

#### Canada

111-76-2

| Chemical name   | NPRI - National Pollutant Release Inventory                   |
|-----------------|---|
| 2-Butoxyethanol | Part 1, Group A Substance                                     |
| 111-76-2        | Part 5 Substance - Volatile Organic Compounds with Additional |
|                 | Reporting Requirements  |
|                 | Part 4 Substance - Criteria Air Contaminants                  |

# **16. OTHER INFORMATION**

# Key or legend to abbreviations and acronyms used in the safety data sheet

### Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

#### ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

### IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen

**OSHA: (Occupational Safety & Health Administration)** 

X - Present

Revision Date Jan-03-2024

# Pursuant to NOM-018-STPS-2015

Page 8/9

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

# **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**