

SAFETY DATA SHEET

Published Date Jan-03-2024

Revision Date Jan-03-2024

Revision Number 2.6

1. IDENTIFICATION

Product identifier Product code **97HTBK Product name Halftone Black Product category** 9700 Series SV Screen Ink Other means of identification None Synonyms Recommended use of the chemical and restrictions on use **Recommended use Industrial Printing Operations** Details of the supplier of the safety data sheet UNITED KINGDOM UNITED STATES Nazdar Company Nazdar Limited 8501 Hedge Lane Terrace Barton Road

Shawnee, KS 66227 Tel: +001-913-422-1888 Tel: +001-800-677-4657 Fax: +001-913-422-2294 www.nazdar.com

Heaton Mersey Stockport, England SK4 3EG Tel: +44 161 442 2111

Emergency telephone number

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887 24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Vapors)	Category 3 - (H331)
Acute toxicity - Inhalation (Dusts/Mists)	Category 3 - (H331)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1 - (H317)

Label elements



Signal word Danger

Hazard statements

H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation

H331 - Toxic if inhaled

Precautionary Statements

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P280 - Wear protective gloves and eye/face protection

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P311 - Call a POISON CENTER or doctor

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Hazards not otherwise classified (HNOC)

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS No.	Weight-%	Trade secret	Note
2-Butoxyethanol	111-76-2	30 - 60	*	
Ethylene glycol monobutyl ether acetate	112-07-2	10 - 30	*	
Resin	Not Available	1 - 5	*	
Carbon black	1333-86-4	1 - 5	*	
Additive	Not Available	0.1 - < 1	*	

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Description of first aid measures

General Advice Eye Contact	Show this safety data sheet to the doctor in attendance. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

StorageKeep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open
flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep
out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Chemical name	ACGIH TLV
2-Butoxyethanol 111-76-2	TWA: 20 ppm
Ethylene glycol monobutyl ether acetate 112-07-2	TWA: 20 ppm
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter
Chemical name	OSHA PEL
2-Butoxyethanol	TWA: 50 ppm

111-76-2	TWA: 30 ppm TWA: 240 mg/m³ Skin
Carbon black 1333-86-4	TWA: 3.5 mg/m ³
Chemical name	OSHA PEL (vacated)
2-Butoxyethanol	TWA: 25 ppm

	TWA: 120 mg/m³ Skin
Carbon black 1333-86-4	TWA: 3.5 mg/m ³

Chemical name	Ontario TWAEV
2-Butoxyethanol	TWA: 20 ppm
111-76-2	
Ethylene glycol monobutyl ether acetate	TWA: 20 ppm
112-07-2	
Carbon black	TWA: 3 mg/m ³ inhalable particulate matter
1333-86-4	

Chemical name	Mexico OEL (TWA)
2-Butoxyethanol 111-76-2	TWA/VLE-PPT: 20 ppm
	TWA/VLE-PPT: 20 ppm
Carbon black 1333-86-4	TWA/VLE-PPT: 3 mg/m ³ inhalable fraction

Appropriate engineering controls

Engineering Measures	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.
Individual protection measures, su	ch as personal protective equipment
Eye/Face Protection	Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.
Skin Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Hand Protection	Chemical resistant protective gloves. Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.
General Hygiene Consideration	s Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical a Physical state Odor	<u>nd chemical properties</u> Liquid Characteristic	Appearance Odor Threshold	Colored No information available
Property	<u>Values</u>	Remarks • Method	_
pH		No data available	
Melting Point / Freezing Point	No information available	No data available	
Boiling Point / Boiling Range	> 149 °C / 300 °F	Densloy Martena Class	
Flash Point	62 °C / 143 °F	Pensky Martens Close	
Evaporation rate		No data available	
Flammability Limit in Air			
Upper flammability limit		No data available	
Lower flammability limit		No data available	
Vapor Pressure		No data available	
Vapor Density	0.00	No data available	
Specific Gravity	0.99	No data available	
Water Solubility		No data available	
Solubility in other solvents Partition coefficient: n-octanol/w	votor.	No data available	
	No information available	No data available	
Autoignition Temperature	No information available	No data available	
Hyphen Kinematic viscosity		No data available	
Dynamic viscosity		No data available	
Explosive Properties	No data available		
Oxidizing Properties	No data available		
Other information			
Photochemically Reactive	No		
Weight Per Gallon (lbs/gal)	8.27		
	0.27		
VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
69.02	No information available	5.71	684.01

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

<u>Hazardous decomposition products</u> Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Specific test data for the substance or mixture is not available. Toxic if inhaled. (based on components).
Eye Contact	Specific test data for the substance or mixture is not available.
Skin Contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Chemical name	Oral LD50
2-Butoxyethanol	= 470 mg/kg (Rat)
111-76-2	
Ethylene glycol monobutyl ether acetate	= 2400 mg/kg (Rat)
112-07-2	
Carbon black	> 15400 mg/kg (Rat)
1333-86-4	

Chemical name	Dermal LD50
2-Butoxyethanol	= 435 mg/kg (Rabbit)
111-76-2	
Ethylene glycol monobutyl ether acetate	= 1500 mg/kg (Rabbit)
112-07-2	
Resin	> 2000 mg/kg (Rat)

Chemical name	Inhalation LC50	
2-Butoxyethanol	= 450 ppm (Rat)4 h	
111-76-2	= 486 ppm (Rat) 4 h	
Ethylene glycol monobutyl ether acetate	> 400 ppm (Rat)4 h	
112-07-2		
Carbon black	> 4.6 mg/m³ (Rat)4 h	
1333-86-4		

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

Specific test data for the substance or mixture is not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Specific test data for the substance or mixture is not available. Causes skin irritation (pain, redness and swelling). (based on components).	
Eye damage/irritation	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components).	
Irritation	Specific test data for the substance or mixture is not available.	
Corrosivity	Specific test data for the substance or mixture is not available.	
Sensitization	Specific test data for the substance or mixture is not available. May cause an allergic skin reaction. (based on components).	
Mutagenic Effects	Specific test data for the substance or mixture is not available.	
Carcinogenic effects	Specific test data for the substance or mixture is not available.	
Reproductive Effects	Specific test data for the substance or mixture is not available.	
STOT - single exposure	Specific test data for the substance or mixture is not available.	
STOT - repeated exposure	Specific test data for the substance or mixture is not available.	
Chronic Toxicity	Specific test data for the substance or mixture is not available	
Aspiration hazard	Specific test data for the substance or mixture is not available.	
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.	
Chemical name	ACGIH	
2-Butoxyethanol 111-76-2	A3	
Ethylene glycol monobutyl ether acetate 112-07-2	A3	
Carbon black 1333-86-4	A3	
	lung	
Chemical name	IARC	

Carbon black	Group 2B
1333-86-4	

Chemical name	OSHA
Carbon black	Х
1333-86-4	

Numerical measures of toxicity - Product Information

Unknown acute toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS documentATEmix (oral)854.20 mg/kgATEmix (dermal)11,295.20 mg/kgATEmix (inhalation-gas)99,999.00ATEmix (inhalation-dust/mist)0.843 mg/lATEmix (inhalation-vapor)5.12 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Specific test data for the substance or mixture is not available.

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	
Ethylene glycol monobutyl ether acetate 112-07-2	72h EC50 Desmodesmus subspicatus: > 500 mg/L	
Chemical name	Fish	
2-Butoxyethanol 111-76-2	96h LC50 Lepomis macrochirus: = 1490 mg/L (static) 96h LC50 Lepomis macrochirus: = 2950 mg/L	
Ethylene glycol monobutyl ether acetate 112-07-2	96h LC50 Oncorhynchus mykiss: 20 - 40 mg/L	
Resin	96h LC50 Oncorhynchus mykiss: = 11.5 mg/L (static)	
Chemical name	Crustacea	
2-Butoxyethanol 111-76-2	48h EC50 Daphnia magna: > 1000 mg/L	
Ethylene glycol monobutyl ether acetate 112-07-2	48h EC50 Daphnia magna: = 37 mg/L	

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Partition coefficient
2-Butoxyethanol 111-76-2	0.81
Ethylene glycol monobutyl ether acetate 112-07-2	1.51

13. DISPOSAL CONSIDERATIONS

Waste treatment methods	
Waste Disposal Methods	Contain and dispose of waste according to local regulations.
Contaminated Packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
	14. TRANSPORT INFORMATION
Note:	This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.
DOT UN/ID no Proper Shipping Name Transport hazard class(es) Packing Group	UN2810 Toxic Liquid, Organic, N.O.S. (2-Butoxyethanol) 6.1 III
ICAO / IATA / IMDG / IMO UN/ID no Proper Shipping Name Transport hazard class(es) Packing Group	UN2810 Toxic Liquid, Organic, N.O.S. (2-Butoxyethanol) 6.1 III

15. REGULATORY INFORMATION

International Inventories

All substances are listed as ACTIVE on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol	111-76-2	30 - 60	1.0
Ethylene glycol monobutyl ether acetate	112-07-2	10 - 30	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Chemical name	CAS No.	Weight-%
Ethylene glycol monobutyl ether acetate	112-07-2	10 - 30

US State Regulations

Chemical name	Massachusetts
2-Butoxyethanol	X
111-76-2	
Carbon black	X
1333-86-4	

	Minnesota Right To Know
2-Butoxyethanol 111-76-2	X
Carbon black 1333-86-4	X

Chemical name	New Jersey
2-Butoxyethanol	Х
111-76-2	
Ethylene glycol monobutyl ether acetate	Х
112-07-2	
Carbon black	Х
1333-86-4	

Chemical name	Pennsylvania
2-Butoxyethanol	X
111-76-2	
Ethylene glycol monobutyl ether acetate	X
112-07-2	
Carbon black	X
1333-86-4	

California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Chemical name	California Proposition 65
Carbon black	Carcinogen
This product contains carbon block in a new receiveble form	Inholation of corbon block is unlikely to cook in from experience to this product

This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product

<u>Canada</u>

Chemical name	NPRI - National Pollutant Release Inventory
2-Butoxyethanol	Part 1, Group A Substance
111-76-2	Part 5 Substance - Volatile Organic Compounds with Additional
	Reporting Requirements
	Part 4 Substance - Criteria Air Contaminants
Ethylene glycol monobutyl ether acetate	Part 5 Substance - Volatile Organic Compounds with Additional
112-07-2	Reporting Requirements
	Part 4 Substance - Criteria Air Contaminants

16. OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend- Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTIONTWATWA (time-weighted average)STELSTEL (Short Term Exposure Limit)CeilingMaximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)
A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen
IARC: (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 2A - Probably Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
NTP: (National Toxicity Program)
Known - Known Carcinogen
Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration) X - Present

Revision Date Jan-03-2024

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet