

# **SAFETY DATA SHEET**

Published DateRevision DateRevision NumberJul-02-2019Jul-02-20192.5

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code
Product name
UV Primer
Product category
Ink Product

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Burton Road
Heaton Mersey

Tel: +001-913-422-1888 Stockport, England SK4 3EG
Tel: +001-800-677-4657 Tel: +44 161 442 2111

Fax: +001-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887

24 Hour Emergency Phone Number

## 2. HAZARDS IDENTIFICATION

#### Classification

Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Flammable liquids	Category 2 - (H225)

### Label elements





Signal Word Danger

## **Hazard Statements**

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H225 - Highly flammable liquid and vapor

### **Precautionary Statements**

P264 - Wash face, hands and any exposed skin thoroughly after handling

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P235 - Keep cool

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

## Hazards not otherwise classified (HNOC)

No information available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Component	CAS-No	Weight %	Trade Secret	Note
Isopropyl alcohol	67-63-0	60 - 100	*	
Glycidoxypropyltrimethoxysilane	2530-83-8	1 - 5	*	

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

#### Description of first aid measures

**General Advice** Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

**Skin Contact** Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

**Inhalation** Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

**Ingestion** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

## Most important symptoms and effects, both acute and delayed

None under normal use conditions.

## Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

## **Suitable Extinguishing Media**

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### **Unsuitable Extinguishing Media**

No information available.

## **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

#### Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

### 7. HANDLING AND STORAGE

## Precautions for safe handling

Handling Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

### Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

open flames, hot surfaces and sources of ignition. Keep container closed when not in use.

Keep out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

### **Exposure limits**

Component	ACGIH TLV
Isopropyl alcohol	TWA: 200 ppm
67-63-0	STEL: 400 ppm

Component	OSHA PEL
Isopropyl alcohol	TWA: 400 ppm
67-63-0	TWA: 980 mg/m <sup>3</sup>

Component	OSHA PEL (vacated)	
Isopropyl alcohol	TWA: 400 ppm	
67-63-0	TWA: 980 mg/m <sup>3</sup>	
	STEL: 500 ppm	
	STEL: 1225 mg/m <sup>3</sup>	

Component	Ontario TWAEV
Isopropyl alcohol	TWA: 200 ppm
67-63-0	STEL: 400 ppm

Component	Mexico OEL (TWA)
Isopropyl alcohol	TWA/VLE-PPT: 400 ppm
67-63-0	TWA/VLE-PPT: 980 mg/m <sup>3</sup>
	STEL/PPT-CT: 500 ppm
	STEL/PPT-CT: 1225 mg/m <sup>3</sup>

### Appropriate engineering controls

Engineering Measures Provide a good standard of general ventilation. Natural ventilation is from doors, windows

\_\_\_\_\_

etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

**Skin Protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Hand Protection Chemical resistant protective gloves.

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene

rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a

chemical-protective glove in practice may be much shorter than the permeation time

determined through testing.

Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as

dimension, color, flexibility.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of

the material.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid Appearance Water-white

Odor No information available Odor Threshold No information available

PropertyValuesRemarks • MethodpHNo data available

Melting Point / Freezing Point

No data available

Boiling Point / Boiling Range > 149 °C / 300 °F

Flash Point 12 °C / 53 °F Tag closed cup

Evaporation rate No data available Flammability Limit in Air

Upper flammability limit
Lower flammability limit
No data available
Vapor Pressure
No data available
Vapor Density
No data available
No data available

Specific Gravity 0.79
Water Solubility No data available

Solubility in other solvents

Partition coefficient: n-octanol/water

Autoignition Temperature

No data available
No data available

Decomposition temperatureNo data availableKinematic viscosityNo data availableDynamic viscosityNo data available

**Explosive Properties**No data available

Oxidizing Properties No data available

**Other Information** 

Photochemically Reactive No Weight Per Gallon (lbs/gal) 6.59

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
98	No information available	6.46	774.64

## 10. STABILITY AND REACTIVITY

#### Reactivity

No information available.

### Chemical stability

Stable under normal conditions.

## Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

### **Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

InhalationSpecific test data for the substance or mixture is not available.Eye ContactSpecific test data for the substance or mixture is not available.Skin ContactSpecific test data for the substance or mixture is not available.IngestionSpecific test data for the substance or mixture is not available.

Component	Oral LD50
Isopropyl alcohol 67-63-0	= 1870 mg/kg (Rat)
Glycidoxypropyltrimethoxysilane 2530-83-8	= 7.01 g/kg(Rat)

Component	Dermal LD50
Isopropyl alcohol	= 4059 mg/kg ( Rabbit )
67-63-0	

Component	Inhalation LC50
Isopropyl alcohol 67-63-0	= 72600 mg/m³(Rat) 4 h
Glycidoxypropyltrimethoxysilane 2530-83-8	> 5.3 mg/L (Rat)4 h

## Information on toxicological effects

**Symptoms** Specific test data for the substance or mixture is not available.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Specific test data for the substance or mixture is not available.

**Eye damage/irritation** Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components).

Irritation

Corrosivity

Specific test data for the substance or mixture is not available.

Specific test data for the substance or mixture is not available.

Specific test data for the substance or mixture is not available.

Mutagenic Effects

Specific test data for the substance or mixture is not available.

Specific test data for the substance or mixture is not available.

Specific test data for the substance or mixture is not available.

Specific test data for the substance or mixture is not available.

Specific test data for the substance or mixture is not available.

STOT - single exposure Specific test data for the substance or mixture is not available. May cause drowsiness or

dizziness. (based on components).

**STOT - repeated exposure**Chronic Toxicity
Aspiration hazard
Specific test data for the substance or mixture is not available.
Specific test data for the substance or mixture is not available.
Specific test data for the substance or mixture is not available.

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA,

IARC or NTP.

## Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

## 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Specific test data for the substance or mixture is not available.

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Isopropyl alcohol	72h EC50 Desmodesmus subspicatus: > 1000 mg/L
67-63-0	96h EC50 Desmodesmus subspicatus: > 1000 mg/L

Component	Fish	
Isopropyl alcohol	96h LC50 Pimephales promelas: = 9640 mg/L (flow-through)	
67-63-0	96h LC50 Lepomis macrochirus: > 1400000 µg/L	
	96h LC50 Pimephales promelas: = 11130 mg/L (static)	

Component Crustacea	
Isopropyl alcohol	48h EC50 Daphnia magna: = 13299 mg/L
67-63-0	

## Persistence and Degradability

No information available.

#### Bioaccumulation

No information available

Component	Partition coefficient
	0.05
67-63-0	

#### Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

### 14. TRANSPORT INFORMATION

Note: This information is not intended to convey all specific transportation requirements relating to

this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and

rules relating to the transportation of the material.

DOT

**UN/ID no.** UN1210

Proper Shipping Name Printing Ink Related Material

Hazard Class 3
Packing Group ||

ICAO / IATA / IMDG / IMO

UN/ID no. UN1210

Proper Shipping Name Printing Ink Related Material

Hazard Class 3
Packing Group ||

## 15. REGULATORY INFORMATION

## **International Inventories**

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

## U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

## Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

## U.S. State Regulations

	Massachusetts
	Right To Know
Isopropyl alcohol	X
67-63-0	

The state of the s	Minnesota Right To Know
Isopropyl alcohol	X
67-63-0	
Glycidoxypropyltrimethoxysilane	X
2530-83-8	

Component	New Jersey Right To Know
Isopropyl alcohol	X

[C7 C3 C	
67-63-0	
Component	Pennsylvania
	Pennsylvania Right To Know

## California Prop. 65

Isopropyl alcohol 67-63-0

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

### Canada

Component	NPRI - National Pollutant Release Inventory
Isopropyl alcohol	Part 5, Individual Substances; Part 4 Substance
67-63-0	

16. OTHER INFORMATION				
HMIS:	Health 2 *	Flammability 3	Reactivity 0	Personal Protection

## Key or legend to abbreviations and acronyms used in the safety data sheet

#### Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**TWA** TWA (time-weighted average) **STEL** STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

#### ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration)

X - Present

**Revision Date** Jul-02-2019

## Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**