

# SAFETY DATA SHEET

Print DateRevision DateRevision NumberMay-30-2015May-30-20151

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code 212
Product name Blue

Product category Ink Product

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Barton Road
Heaton Mersey

Tel: 1-913-422-1888 Stockport, England SK4 3EG
Tel: 1-800-677-4657 Tel: +44 161 442 2111

Fax: 1-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: 1-800-424-9300 Outside USA: Chemtrec: 1-703-527-3887

24 Hour Emergency Phone Number

# 2. HAZARDS IDENTIFICATION

### Classification

Acute toxicity - Oral	Category 4 - (H302)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin Corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)

# Label elements



Signal Word Warning

#### **Hazard Statements**

H302 - Harmful if swallowed H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

212 - Blue

### Hazards not otherwise classified (HNOC)

May be harmful in contact with skin. Combustible liquid.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Component	CAS-No	Weight %	Trade Secret	Note
2-Butoxyethanol	111-76-2	30 - 60	*	
Talc	14807-96-6	30 - 60	*	
Crystalline silica (cristobalite)	14464-46-1	< 0.5	*	

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

# **Description of first aid measures**

**General Advice** Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

**Skin Contact** Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

Inhalation Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

**Ingestion** DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

### Most important symptoms and effects, both acute and delayed

None under normal use conditions.

# Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

### **Suitable Extinguishing Media**

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### **Unsuitable Extinguishing Media**

No information available.

### **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

# **Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

# Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

**Handling** Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

open flames, hot surfaces and sources of ignition. Keep container closed when not in use.

Keep out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

### **Exposure limits**

Component	ACGIH TLV
2-Butoxyethanol	TWA: 20 ppm
111-76-2	
Talc	TWA: 2 mg/m³ (particulate matter)
14807-96-6	- "
Crystalline silica (cristobalite)	TWA: 0.025 mg/m³ (respirable fraction)
14464-46-1	- , ,

Component	OSHA PEL
2-Butoxyethanol	TWA: 25 ppm
111-76-2	TWA: 120 mg/m <sup>3</sup>
	TWA: 50 ppm
	TWA: 240 mg/m <sup>3</sup>
	Skin
Talc	TWA: 2 mg/m³ (respirable dust)
14807-96-6	
Crystalline silica (cristobalite)	TWA: 0.05 mg/m³ (respirable dust)
14464-46-1	

Component	Ontario TWAEV
2-Butoxyethanol 111-76-2	TWA: 20 ppm
Talc 14807-96-6	TWA: 2 mg/m³ (respirable)
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.05 mg/m³ (respirable)

Component	Mexico OEL (TWA)
2-Butoxyethanol	TWA/LMPE-PPT: 26 ppm
111-76-2	TWA/LMPE-PPT: 120 mg/m <sup>3</sup>
	STEL/LMPE-CT: 75 ppm

	STEL/LMPE-CT: 360 mg/m <sup>3</sup>
Talc 14807-96-6	TWA/LMPE-PPT: 2 mg/m³ (respirable fraction)
Crystalline silica (cristobalite) 14464-46-1	TWA/LMPE-PPT: 0.05 mg/m³ (respirable fraction)

#### Appropriate engineering controls

Provide a good standard of general ventilation. Natural ventilation is from doors, windows **Engineering Measures** 

etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In

case of insufficient ventilation, wear suitable respiratory equipment.

# Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear **Eye/face Protection** 

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, Skin Protection

as appropriate, to prevent skin contact.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved **Respiratory Protection** 

respiratory protection should be worn. Respiratory protection must be provided in

accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Colored Liquid **Physical State** Liquid Appearance

Odor Characteristic Odor Threshold No information available

Property Values Remarks • Method

No data available

Melting point/freezing point No data available

> 149 °C / 300 °F **Boiling point/Boiling Range Flash Point** 77 °C / 170 °F Setaflash closed cup

No data available

**Evaporation rate** Flammability Limit in Air

**Upper flammability limit** No data available

Lower flammability limit No data available

**Vapor Pressure** No data available Vapor Density No data available

**Specific Gravity** 1.28 Water Solubility No data available

Solubility in other solvents No data available Partition coefficient: n-octanol/water No data available

**Autoignition Temperature** No data available **Decomposition temperature** No data available

Kinematic viscosity No data available **Dynamic viscosity** No data available

No data available **Explosive Properties Oxidizing Properties** No data available

Other Information

**Photochemically Reactive** No

### Weight Per Gallon (lbs/gal) 10.68

VOC by weight % (less water)	VOC by volume %	VOC lbs/gal	VOC grams/liter
	(less water)	(less water)	(less water)
37.58	53.37	4.02	` 481.46 <i>´</i>

# 10. STABILITY AND REACTIVITY

### Reactivity

No information available.

### Chemical stability

Stable under normal conditions.

# Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

### **Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

InhalationThere is no data for this product.Eye ContactThere is no data for this product.Skin ContactThere is no data for this product.IngestionThere is no data for this product.

Component	Oral LD50
2-Butoxyethanol 111-76-2	470 mg/kg (Rat)

Component	LD50 Dermal
2-Butoxyethanol	2270 mg/kg (Rat)
111-76-2	220 mg/kg(Rabbit)

Component	Inhalation LC50
2-Butoxyethanol	2.21 mg/L (Rat) 4 h
111-76-2	450 ppm (Rat) 4 h

### Information on toxicological effects

**Symptoms** There is no data for this product.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation There is no data for this product. Eye damage/irritation There is no data for this product. Irritation There is no data for this product. There is no data for this product. Corrosivity There is no data for this product. Sensitisation There is no data for this product. **Mutagenic Effects** There is no data for this product. **Reproductive Effects** There is no data for this product. STOT - single exposure STOT - repeated exposure There is no data for this product. **Chronic Toxicity** There is no data for this product

**Aspiration hazard** There is no data for this product.

**Carcinogenicity**The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH
2-Butoxyethanol	A3
111-76-2	

Component	IARC
Crystalline silica (cristobalite)	Group 1

Component	OSHA
Crystalline silica (cristobalite)	X
14464-46-1	

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 1,251.00 mg/kg

 ATEmix (dermal)
 2,927.00 mg/kg mg/l

ATEmix (inhalation-dust/mist) 5.88 mg/l ATEmix (inhalation-vapor) 29.00 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Fish
2-Butoxyethanol	96h LC50 Lepomis macrochirus: 1490 mg/L [static] 96h LC50 Lepomis macrochirus: 2950 mg/L
Talc 14807-96-6	96h LC50 Brachydanio rerio: >100 g/L [semi-static]

Component	Crustacea
2-Butoxyethanol	24h EC50 Daphnia magna: 1698 - 1940 mg/L
111-76-2	48h EC50 Daphnia magna: >1000 mg/L

### Persistence and Degradability

No information available.

### **Bioaccumulation**

No information available.

Component	Partition coefficient
2-Butoxyethanol	0.81
111-76-2	

# Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. TRANSPORT INFORMATION

DOTNot regulatedProper Shipping NamePrinting Ink

Proper Shipping Name

Not Regulated
Printing Ink

# 15. REGULATORY INFORMATION

### **International Inventories**

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

# U.S. Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
2-Butoxyethanol	111-76-2	30 - 60	1.0

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

# U.S. State Regulations

Component	Massachusetts Right To Know
2-Butoxyethanol 111-76-2	X
Talc 14807-96-6	X
Crystalline silica (cristobalite) 14464-46-1	x

Component	Minnesota Right To Know
2-Butoxyethanol 111-76-2	X
Talc 14807-96-6	X
Crystalline silica (cristobalite) 14464-46-1	X

Component	New Jersey Right To Know
2-Butoxyethanol	X
111-76-2	
Talc	X
14807-96-6	
Crystalline silica (cristobalite)	X
14464-46-1	

Component	Pennsylvania Right To Know
2-Butoxyethanol 111-76-2	X
Talc 14807-96-6	X
Crystalline silica (cristobalite)	X

14464-46-1		
1 14404-40-1		

### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

### Canada

Component	NPRI - National Pollutant Release Inventory
2-Butoxyethanol	Part 1, Group A Substance
111-76-2	Part 5, Individual Substances Part 4 Substance as set out in
	Section 65 of the List of Toxic Substances in Schedule 1 of the
	Canadian Environmental Protection Act, 1999

# **16. OTHER INFORMATION**

HMIS:HealthFlammabilityReactivityPersonal Protection2 \*20X

### Key or legend to abbreviations and acronyms used in the safety data sheet

### Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

### ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date May-30-2015

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of MSDS**