

SAFETY DATA SHEET

Print DateRevision DateRevision NumberMay-31-2015May-30-20151

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code 89410
Product name Yellow

Product category 8900 Series SuperSet Thermo-Set Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Burton Road
Heaton Mersey

Tel: 1-913-422-1888 Stockport, England SK4 3EG
Tel: 1-800-677-4657 Tel: +44 161 442 2111

Fax: 1-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: 1-800-424-9300

Outside USA: Chemtrec: 1-703-527-3887 24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Flammable liquids Category 3 - (H226)

Label elements



Signal Word Warning

Hazard Statements

H226 - Flammable liquid and vapor EUH208 - May produce an allergic reaction

Precautionary Statements

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Revision Date May-30-2015

89410 - Yellow

Hazards not otherwise classified (HNOC)

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Ingestion

Component	CAS-No	Weight %	Trade Secret	Note
Titanium dioxide	13463-67-7	1 - 5	*	
Naphtha (petroleum), heavy aromatic	64742-94-5	1 - 5	*	
Diethylene glycol monobutyl ether	112-34-5	1 - 5	*	
Naphthalene (constituent)	91-20-3	< 0.5	*	1

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

4. FIRST AID MEASURES

Description of first aid measures

Show this safety data sheet to the doctor in attendance. **General Advice**

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

> contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention. Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

Inhalation stopped, administer artificial respiration. Get medical attention immediately.

DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

open flames, hot surfaces and sources of ignition. Keep container closed when not in use.

Keep out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Component	ACGIH TLV
Titanium dioxide	TWA: 10 mg/m ³
13463-67-7	-
Naphthalene (constituent)	TWA: 10 ppm
91-20-3	STEL: 15 ppm
	Skin

Component	OSHA PEL
Titanium dioxide	TWA: 10 mg/m³ (total dust)
13463-67-7	TWA: 15 mg/m³ (total dust)
Naphthalene (constituent)	TWA: 10 ppm
91-20-3	TWA: 50 mg/m ³
	STEL: 15 ppm
	STEL: 75 mg/m ³

Component	Ontario TWAEV	
Titanium dioxide	TWA: 10 mg/m³ (total dust)	
13463-67-7		
Naphthalene (constituent)	TWA: 10 ppm	
91-20-3	STEL: 15 ppm	
	Skin	

Component	Mexico OEL (TWA)
Titanium dioxide	TWA/LMPE-PPT: 10 mg/m³ (as Ti)
13463-67-7	STEL/LMPE-CT: 20 mg/m³ (as Ti)
Naphthalene (constituent)	TWA/LMPE-PPT: 10 ppm
91-20-3	TWA/LMPE-PPT: 50 mg/m ³
	STEL/LMPE-CT: 15 ppm
	STEL/LMPE-CT: 75 mg/m ³

Appropriate engineering controls

Engineering Measures Provide a good standard of general ventilation. Natural ventilation is from doors, windows

etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In

case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face Protection Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

Skin Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in

accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid Appearance Colored Liquid Odor Throshold No information available

Odor Characteristic Odor Threshold No information available

PropertyValuesRemarks • MethodpHNo data available

Melting point/freezing point

No data available

No data available

Boiling point/Boiling Range > 149 °C / 300 °F

Flash Point 46 °C / 115 °F Pensky Martens Closed Cup (PMCC)

Evaporation rate No data available

Flammability Limit in Air

Upper flammability limitNo data availableLower flammability limitNo data availableVapor PressureNo data available

Vapor Density No data available

Specific Gravity 1.2

Water SolubilityNo data availableSolubility in other solventsNo data availablePartition coefficient: n-octanol/waterNo data availableAutoignition TemperatureNo data availableDecomposition temperatureNo data available

Kinematic viscosity
No data available

Dynamic viscosity
No data available

Explosive Properties

Oxidizing Properties

No data available
No data available

Other Information

Photochemically Reactive No Weight Per Gallon (lbs/gal) 10.04

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
6.16	7.97	0-1	

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

InhalationThere is no data for this product.Eye ContactThere is no data for this product.Skin ContactThere is no data for this product.IngestionThere is no data for this product.

Component	Oral LD50
Titanium dioxide 13463-67-7	>10000 mg/kg(Rat)
Naphtha (petroleum), heavy aromatic 64742-94-5	>5000 mg/kg (Rat)
Diethylene glycol monobutyl ether 112-34-5	3384 mg/kg (Rat)
Naphthalene (constituent) 91-20-3	490 mg/kg (Rat)

Component	LD50 Dermal
Naphtha (petroleum), heavy aromatic 64742-94-5	>2000 mg/kg(Rabbit)
Diethylene glycol monobutyl ether 112-34-5	2700 mg/kg(Rabbit)
Naphthalene (constituent) 91-20-3	>2500 mg/kg(Rat) >20 g/kg(Rabbit)

Component	Inhalation LC50
Naphtha (petroleum), heavy aromatic 64742-94-5	>590 mg/m³(Rat)4 h
Naphthalene (constituent) 91-20-3	>340 mg/m³(Rat)1 h

Information on toxicological effects

Symptoms There is no data for this product.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationThere is no data for this product.Eye damage/irritationThere is no data for this product.IrritationThere is no data for this product.CorrosivityThere is no data for this product.SensitisationThere is no data for this product.

Constitution of the case is the product

Mutagenic EffectsThere is no data for this product.Reproductive EffectsThere is no data for this product.STOT - single exposureThere is no data for this product.STOT - repeated exposureThere is no data for this product.Chronic ToxicityThere is no data for this product.Aspiration hazardThere is no data for this product.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	IARC
Titanium dioxide	Group 2B
13463-67-7	
Naphthalene (constituent)	Group 2B
91-20-3	·

Component	NTP
Naphthalene (constituent)	Reasonably Anticipated
91-20-3	

Component	OSHA
Titanium dioxide 13463-67-7	X
Naphthalene (constituent) 91-20-3	X

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 49,166.00 mg/kg **ATEmix (dermal)** 52,194.00 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Diethylene glycol monobutyl ether 112-34-5	96h EC50 Desmodesmus subspicatus: >100 mg/L
Naphthalene (constituent) 91-20-3	72h EC50 Skeletonema costatum: 0.4 mg/L

Component	Fish
Diethylene glycol monobutyl ether	96h LC50 Lepomis macrochirus: 1300 mg/L [static]
112-34-5	
Naphthalene (constituent)	96h LC50 Oncorhynchus mykiss: 0.91 - 2.82 mg/L [static]
91-20-3	96h LC50 Pimephales promelas: 5.74 - 6.44 mg/L [flow-through]
	96h LC50 Oncorhynchus mykiss: 1.6 mg/L [flow-through]
	96h LC50 Pimephales promelas: 1.99 mg/L [static]
	96h LC50 Lepomis macrochirus: 31.0265 mg/L [static]

Component	Crustacea
Diethylene glycol monobutyl ether	24h EC50 Daphnia magna: 2850 mg/L
112-34-5	48h EC50 Daphnia magna: >100 mg/L
Naphthalene (constituent)	48h EC50 Daphnia magna: 1.09 - 3.4 mg/L [static]
91-20-3	48h EC50 Daphnia magna: 1.96 mg/L [Flow through]
	48h LC50 Daphnia magna: 2.16 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Component	Partition coefficient
Naphtha (petroleum), heavy aromatic 64742-94-5	4.5
Naphthalene (constituent) 91-20-3	3.3

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. TRANSPORT INFORMATION

DOT In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not

regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language

Part 1.33].

UN/ID no. UN1210 Proper Shipping Name Printing Ink

Hazard Class 3
Packing Group III

ICAO / IATA / IMDG / IMO

UN/ID no. UN1210
Proper Shipping Name Printing Ink

Hazard Class 3
Packing Group III

15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

of chemicale which are cabject to the reporting requirements of the rote and this red of the code of red characteristics, i art or z.			
Component	CAS-No	Weight %	SARA 313 - Threshold
			Values
Diethylene glycol monobutyl ether	112-34-5	1 - 5	1.0
Naphthalene (constituent)	91-20-3	< 0.5	0.1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Component	CAS-No	Weight %
Diethylene glycol monobutyl ether	112-34-5	1 - 5

U.S. State Regulations

Component	Massachusetts Right To Know
Titanium dioxide 13463-67-7	X
Naphthalene (constituent) 91-20-3	X

Component	Minnesota Right To Know
Titanium dioxide 13463-67-7	X
Naphthalene (constituent) 91-20-3	X

Component	New Jersey Right To Know
Titanium dioxide 13463-67-7	X
Diethylene glycol monobutyl ether 112-34-5	X
Naphthalene (constituent) 91-20-3	X

Component	Pennsylvania Right To Know
Titanium dioxide 13463-67-7	X
Diethylene glycol monobutyl ether 112-34-5	X
Naphthalene (constituent) 91-20-3	X

California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Component	California Prop. 65
Titanium dioxide	Carcinogen
Naphthalene (constituent)	Carcinogen

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Canada

Component	NPRI - National Pollutant Release Inventory
Naphtha (petroleum), heavy aromatic	Part 5, Other Groups and Mixtures Part 4 Substance as set out in
64742-94-5	Section 65 of the List of Toxic Substances in Schedule 1 of the
	Canadian Environmental Protection Act, 1999
Diethylene glycol monobutyl ether	Part 5, Other Groups and Mixtures Part 4 Substance as set out in
112-34-5	Section 65 of the List of Toxic Substances in Schedule 1 of the
	Canadian Environmental Protection Act, 1999
Naphthalene (constituent)	Part 1, Group A Substance Part 4 Substance as set out in Section
91-20-3	65 of the List of Toxic Substances in Schedule 1 of the Canadian
	Environmental Protection Act, 1999

16. OTHER INFORMATION				
HMIS:	Health	Flammability	Reactivity	Personal Protection

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

89410 - Yellow Revision Date May-30-2015

Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date May-30-2015

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of MSDS