

Published Date
Nov-28-2023

Revision Date
Nov-28-2023

Revision Number
2.7

1. IDENTIFICATION

Product identifier

Product code 8883
Product name Magenta Toner
Product category 8800 Series SV Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Industrial Printing Operations

Details of the supplier of the safety data sheet

UNITED STATES	UNITED KINGDOM
Nazdar Company	Nazdar Limited
8501 Hedge Lane Terrace	Barton Road
Shawnee, KS 66227	Heaton Mersey
Tel: +001-913-422-1888	Stockport, England SK4 3EG
Tel: +001-800-677-4657	Tel: +44 161 442 2111
Fax: +001-913-422-2294	
www.nazdar.com	

Emergency telephone number

USA: Chemtrec: +001-800-424-9300
Outside USA: Chemtrec: +001-703-527-3887
24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Carcinogenicity	Category 2 - (H351)
Aspiration hazard	Category 1 - (H304)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 3 - (H226)

Label elements



Signal word
Danger

Hazard statements

H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways
 H315 - Causes skin irritation
 H318 - Causes serious eye damage
 H332 - Harmful if inhaled
 H351 - Suspected of causing cancer
 H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a POISON CENTER or doctor
 P331 - Do NOT induce vomiting
 P403 + P235 - Store in a well-ventilated place. Keep cool

Hazards not otherwise classified (HNOC)

Harmful to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS No.	Weight-%	Trade secret	Note
2-Butoxyethanol	111-76-2	30 - 60	*	
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	10 - 30	*	
Butyrolactone	96-48-0	10 - 30	*	
Naphthalene (constituent)	91-20-3	1 - 5	*	1
Ethylene glycol monopropyl ether	2807-30-9	1 - 5	*	
1,2,4-Trimethylbenzene (constituent)	95-63-6	0.1 - < 1	*	1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note

1. Hazardous Constituent contained in Complex Substance(s) required for disclosure

4. FIRST-AID MEASURES

Description of first aid measures**General Advice**

Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO₂). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

Incompatible Products

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Chemical name	ACGIH TLV
2-Butoxyethanol 111-76-2	TWA: 20 ppm
Naphthalene (constituent) 91-20-3	TWA: 10 ppm Skin
1,2,4-Trimethylbenzene (constituent)	TWA: 10 ppm

95-63-6	
Chemical name	OSHA PEL
2-Butoxyethanol 111-76-2	TWA: 50 ppm TWA: 240 mg/m ³ Skin
Naphthalene (constituent) 91-20-3	TWA: 10 ppm TWA: 50 mg/m ³
Chemical name	OSHA PEL (vacated)
2-Butoxyethanol 111-76-2	TWA: 25 ppm TWA: 120 mg/m ³ Skin
Naphthalene (constituent) 91-20-3	TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
Chemical name	Ontario TWAEV
2-Butoxyethanol 111-76-2	TWA: 20 ppm
Naphthalene (constituent) 91-20-3	TWA: 10 ppm Skin
Ethylene glycol monopropyl ether 2807-30-9	TWA: 25 ppm TWA: 110 mg/m ³ Skin
Chemical name	Mexico OEL (TWA)
2-Butoxyethanol 111-76-2	TWA/VLE-PPT: 20 ppm
Naphthalene (constituent) 91-20-3	TWA/VLE-PPT: 10 ppm STEL/PPT-CT: 15 ppm

Appropriate engineering controls

Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Wear safety glasses with side shields (or goggles). If splashes are likely to occur: Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.

Skin Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Hand Protection

Chemical resistant protective gloves.
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other
Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.
Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Appearance	Colored
Odor	Characteristic	Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH		No data available
Melting Point / Freezing Point	No information available	No data available
Boiling Point / Boiling Range	> 149 °C / 300 °F	
Flash Point	49 °C / 120 °F	Pensky Martens Closed Cup (PMCC)
Evaporation rate		No data available
Flammability Limit in Air		
Upper flammability limit		No data available
Lower flammability limit		No data available
Vapor Pressure		No data available
Vapor Density		No data available
Specific Gravity	1.01	
Water Solubility		No data available
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition Temperature	No information available	No data available
Hyphen		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available
Explosive Properties	No data available	
Oxidizing Properties	No data available	

Other information

Photochemically Reactive	Yes
Weight Per Gallon (lbs/gal)	8.4

VOC by weight % (less water)	VOC by volume % (less water)	VOC lbs/gal (less water)	VOC grams/liter (less water)
73.66	76.32	6.2	742.44

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO₂). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Specific test data for the substance or mixture is not available. Harmful if inhaled. (based on components).
Eye Contact	Specific test data for the substance or mixture is not available.
Skin Contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Chemical name	Oral LD50
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)
Butyrolactone 96-48-0	= 1540 mg/kg (Rat)
Naphthalene (constituent) 91-20-3	= 1110 mg/kg (Rat)
Ethylene glycol monopropyl ether 2807-30-9	= 3089 mg/kg (Rat)
1,2,4-Trimethylbenzene (constituent) 95-63-6	= 3280 mg/kg (Rat)

Chemical name	Dermal LD50
2-Butoxyethanol 111-76-2	= 435 mg/kg (Rabbit)
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 2000 mg/kg (Rabbit)
Butyrolactone 96-48-0	> 5640 mg/kg (Rabbit)
Naphthalene (constituent) 91-20-3	= 1120 mg/kg (Rabbit)
Ethylene glycol monopropyl ether 2807-30-9	= 870 mg/kg (Rabbit)
1,2,4-Trimethylbenzene (constituent) 95-63-6	> 3160 mg/kg (Rabbit)

Chemical name	Inhalation LC50
2-Butoxyethanol 111-76-2	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 590 mg/m ³ (Rat) 4 h
Butyrolactone 96-48-0	> 5100 mg/m ³ (Rat) 4 h
Naphthalene (constituent) 91-20-3	> 0.4 mg/L (Rat) 4 h
Ethylene glycol monopropyl ether 2807-30-9	= 1530 ppm (Rat) 7 h
1,2,4-Trimethylbenzene (constituent) 95-63-6	= 18 g/m ³ (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Specific test data for the substance or mixture is not available.
-----------------	---

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Specific test data for the substance or mixture is not available. Causes skin irritation (pain, redness and swelling). (based on components).
Eye damage/irritation	Specific test data for the substance or mixture is not available. Causes serious eye damage. (based on components).
Irritation	Specific test data for the substance or mixture is not available.
Corrosivity	Specific test data for the substance or mixture is not available.
Sensitization	Specific test data for the substance or mixture is not available.
Mutagenic Effects	Specific test data for the substance or mixture is not available.
Carcinogenic effects	Specific test data for the substance or mixture is not available. Suspected of causing cancer. (based on components).
Reproductive Effects	Specific test data for the substance or mixture is not available.
STOT - single exposure	Specific test data for the substance or mixture is not available.
STOT - repeated exposure	Specific test data for the substance or mixture is not available.
Chronic Toxicity	Specific test data for the substance or mixture is not available.
Aspiration hazard	Specific test data for the substance or mixture is not available. May be fatal if swallowed and enters airways. (based on components).
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH
2-Butoxyethanol 111-76-2	A3
Naphthalene (constituent) 91-20-3	A3

Chemical name	IARC
Naphthalene (constituent) 91-20-3	Group 2B

Chemical name	NTP
Naphthalene (constituent) 91-20-3	Reasonably Anticipated

Chemical name	OSHA
Naphthalene (constituent) 91-20-3	X

Numerical measures of toxicity - Product Information

Unknown acute toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	2,720.10 mg/kg
ATEmix (dermal)	90,991.80 mg/kg
ATEmix (inhalation-gas)	99,999.00
ATEmix (inhalation-dust/mist)	4.57 mg/l
ATEmix (inhalation-vapor)	33.50 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Specific test data for the substance or mixture is not available. Harmful to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants
Butyrolactone	96h EC50 Desmodesmus subspicatus: = 79 mg/L

96-48-0	72h EC50 Desmodesmus subspicatus: = 360 mg/L
Chemical name	Fish
2-Butoxyethanol 111-76-2	96h LC50 Lepomis macrochirus: = 1490 mg/L (static) 96h LC50 Lepomis macrochirus: = 2950 mg/L
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	96h LC50 Pimephales promelas: = 19 mg/L (static) 96h LC50 Oncorhynchus mykiss: = 2.34 mg/L 96h LC50 Lepomis macrochirus: = 1740 mg/L (static) 96h LC50 Pimephales promelas: = 45 mg/L (flow-through) 96h LC50 Pimephales promelas: = 41 mg/L
Butyrolactone 96-48-0	96h LC50 Lepomis macrochirus: = 56 mg/L (static)
Naphthalene (constituent) 91-20-3	96h LC50 Oncorhynchus mykiss: = 1.6 mg/L (flow-through) 96h LC50 Oncorhynchus mykiss: 0.91 - 2.82 mg/L (static) 96h LC50 Pimephales promelas: = 1.99 mg/L (static) 96h LC50 Lepomis macrochirus: = 31.0265 mg/L (static) 96h LC50 Pimephales promelas: 5.74 - 6.44 mg/L (flow-through)
Ethylene glycol monopropyl ether 2807-30-9	96h LC50 Pimephales promelas: > 5000 mg/L (static)
1,2,4-Trimethylbenzene (constituent) 95-63-6	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L (flow-through)

Chemical name	Crustacea
2-Butoxyethanol 111-76-2	48h EC50 Daphnia magna: > 1000 mg/L
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	48h EC50 Daphnia magna: = 0.95 mg/L
Butyrolactone 96-48-0	48h EC50 Daphnia magna Straus: > 500 mg/L
Naphthalene (constituent) 91-20-3	48h EC50 Daphnia magna: 1.09 - 3.4 mg/L Static 48h EC50 Daphnia magna: = 1.96 mg/L Flow through 48h LC50 Daphnia magna: = 2.16 mg/L
1,2,4-Trimethylbenzene (constituent) 95-63-6	48h EC50 Daphnia magna: = 6.14 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Partition coefficient
2-Butoxyethanol 111-76-2	0.81
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	2.9 - 6.1
Butyrolactone 96-48-0	-0.566
Naphthalene (constituent) 91-20-3	3.6
1,2,4-Trimethylbenzene (constituent) 95-63-6	3.63

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Waste Disposal Methods**

Contain and dispose of waste according to local regulations.

Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

Note:

This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

DOT

In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33].

UN/ID no	UN1210
Proper Shipping Name	Printing Ink
Transport hazard class(es)	3
Packing Group	III

ICAO / IATA / IMDG / IMO

UN/ID no	UN1210
Proper Shipping Name	Printing Ink
Transport hazard class(es)	3
Packing Group	III

15. REGULATORY INFORMATION

International Inventories

All substances are listed as ACTIVE on the TSCA Inventory. For further information, please contact: . Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol	111-76-2	30 - 60	1.0
Naphthalene (constituent)	91-20-3	1 - 5	0.1
Ethylene glycol monopropyl ether	2807-30-9	1 - 5	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Chemical name	CAS No.	Weight-%
Naphthalene (constituent)	91-20-3	1 - 5
Ethylene glycol monopropyl ether	2807-30-9	1 - 5
Xylenes (o-, m-, p- isomers)	1330-20-7	0.1 - < 1

US State Regulations

Chemical name	Massachusetts
2-Butoxyethanol 111-76-2	X
Naphthalene (constituent) 91-20-3	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X

Chemical name	Minnesota Right To Know
2-Butoxyethanol 111-76-2	X
Naphthalene (constituent) 91-20-3	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X

Chemical name	New Jersey
2-Butoxyethanol 111-76-2	X
Naphthalene (constituent) 91-20-3	X
Ethylene glycol monopropyl ether 2807-30-9	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X

Chemical name	Pennsylvania
2-Butoxyethanol 111-76-2	X
Naphthalene (constituent) 91-20-3	X
Ethylene glycol monopropyl ether 2807-30-9	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X

California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Chemical name	California Proposition 65
Naphthalene (constituent)	Carcinogen

Canada

Chemical name	NPRI - National Pollutant Release Inventory
2-Butoxyethanol 111-76-2	Part 1, Group A Substance Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants
Butyrolactone 96-48-0	Part 4 Substance - Criteria Air Contaminants
Naphthalene (constituent) 91-20-3	Part 1, Group A Substance Part 4 Substance - Criteria Air Contaminants
Ethylene glycol monopropyl ether 2807-30-9	Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants
1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 1, Group A Substance Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants

16. OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans
Group 2A - Probably Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen
Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date Nov-28-2023

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet