



Print Date May-30-2015 Revision Date May-30-2015 Revision Number

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier
Product code
Product name
Product category

1675 Super Opaque White 1600 PowerPrint® Series UV Screen Ink

Other means of identification Synonyms

Recommended use of the chemical and restrictions on useRecommended usePrinting operations

None

## Details of the supplier of the safety data sheet

UNITED STATES Nazdar Company 8501 Hedge Lane Terrace Shawnee, KS 66227 Tel: 1-913-422-1888 Tel: 1-800-677-4657 Fax: 1-913-422-2294 www.nazdar.com UNITED KINGDOM Nazdar Limited Barton Road Heaton Mersey Stockport, England SK4 3EG Tel: +44 161 442 2111

### Emergency telephone number

USA: Chemtrec: 1-800-424-9300 Outside USA: Chemtrec: 1-703-527-3887 24 Hour Emergency Phone Number

# 2. HAZARDS IDENTIFICATION

### **Classification**

Skin Corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1 - (H317)
Reproductive toxicity	Category 2 - (H361)

#### Label elements



Warning

#### Hazard Statements

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H361 - Suspected of damaging fertility or the unborn child

P280 - Wear eye protection/ face protection

P280 - Wear protective gloves/protective clothing/eye protection/face protection

#### Hazards not otherwise classified (HNOC)

No information available.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Component	CAS-No	Weight %	Trade Secret	Note
Titanium dioxide	13463-67-7	10 - 30	*	
Acrylated Monomer	Trade Secret	10 - 30	*	
Glycol Ether Acrylate	Trade Secret	10 - 30	*	
Acrylated Monomer	Trade Secret	10 - 30	*	
Photoinitiator	Trade Secret	1 - 5	*	
Triethanolamine	102-71-6	1 - 5	*	

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

#### Description of first aid measures

General Advice Eye Contact	Show this safety data sheet to the doctor in attendance. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
Ingestion	DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

#### Notes to Physician

Treat symptomatically.

# **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Unsuitable Extinguishing Media

No information available.

# Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions. Hazardous polymerization may take place during a fire due to heat. Closed containers could violently rupture.

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

#### Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

#### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

 Handling
 Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

 Conditions for safe storage, including any incompatibilities
 Storage

 Keep at temperatures between 18°-32°C (65°-90°F). Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

#### **Exposure limits**

Component	ACGIH TLV
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>
13463-67-7	
Triethanolamine	TWA: 5 mg/m <sup>3</sup>
102-71-6	

Component	OSHA PEL
Titanium dioxide	TWA: 10 mg/m <sup>3</sup> (total dust)
13463-67-7	TWA: 15 mg/m <sup>3</sup> (total dust)

Component	Ontario TWAEV
Titanium dioxide	TWA: 10 mg/m <sup>3</sup> (total dust)
13463-67-7	
Triethanolamine	TWA: 0.5 ppm
102-71-6	TWA: 3.1 mg/m <sup>3</sup>
102-71-0	TWA. 3.1 light

Component	Mexico OEL (TWA)
Titanium dioxide	TWA/LMPE-PPT: 10 mg/m <sup>3</sup> (as Ti)
13463-67-7	STEL/LMPE-CT: 20 mg/m <sup>3</sup> (as Ti)

# Appropriate engineering controls

Engineering Measures	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.
Individual protection measures, suc	h as personal protective equipment
Eye/face Protection	Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.
Skin Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid	Appearance	Colored Liquid
Odor	Mild Sweet Acrylic	Odor Threshold	No information available
Property_	Values	Remarks • Method	
рН		No data available	
Melting point/freezing point		No data available	
Boiling point/Boiling Range	> 149 °C / 300 °F		
Flash Point	> 94 °C / > 201 °F	Pensky Martens Close	ed Cup (PMCC)
Evaporation rate		No data available	
Flammability Limit in Air			
Upper flammability limit		No data available	
Lower flammability limit		No data available	
Vapor Pressure		No data available	
Vapor Density		No data available	
Specific Gravity	1.31		
Water Solubility		No data available	
Solubility in other solvents Partition coefficient: n-octanol/water		No data available	
		No data available	
Autoignition Temperature		No data available	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	
Explosive Properties	No data available		
Oxidizing Properties	No data available		
Other Information			
Photochemically Reactive	No		
Weight Per Gallon (lbs/gal)	10.89		
VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
0-1	0-1	0-1	0-1
	10. STABILITY AN	DREACTIVITY	

## Reactivity

No information available.

# Chemical stability

Stable under normal conditions.

#### Possibility of Hazardous Reactions

None under normal processing. Do not store for longer periods at temperatures above 93°C (200°F).

#### Conditions to avoid

Temperatures above 93 °C / 200 °F. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

## Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation	There is no data for this product.
Eye Contact	There is no data for this product.
Skin Contact	There is no data for this product.
Ingestion	There is no data for this product.

>10000 mg/kg (Rat)	
5 g/kg (Rat)	
4660 µL/kg (Rat)	
5190 μL/kg (Rat)	
4190 mg/kg (Rat)	
· · ·	

Component	LD50 Dermal
Acrylated Monomer	3600 µL/kg (Rabbit)
Glycol Ether Acrylate	2540 μL/kg (Rabbit)
Acrylated Monomer	5000 mg/kg (Rabbit)
Triethanolamine 102-71-6	>16 mL/kg (Rat) >2000 mg/kg (Rabbit)

#### Information on toxicological effects

Symptoms

There is no data for this product.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure\_

Skin corrosion/irritation Eye damage/irritation	There is no data for this product. There is no data for this product.
Irritation	There is no data for this product.
Corrosivity	There is no data for this product.
Sensitisation	There is no data for this product.
Mutagenic Effects	There is no data for this product.

Reproductive Effects	There is no data for this product.
STOT - single exposure	There is no data for this product.
STOT - repeated exposure	There is no data for this product.
Chronic Toxicity	There is no data for this product
Aspiration hazard	There is no data for this product.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	IARC
Titanium dioxide	Group 2B
13463-67-7	

Component	OSHA
Titanium dioxide	Х
13463-67-7	

## Numerical measures of toxicity - Product Information

#### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	15,201.00 n		
ATEmix (dermal)	31,406.00 n	ng/kg	mg/l

# **12. ECOLOGICAL INFORMATION**

# Ecotoxicity

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Triethanolamine	96h EC50 Desmodesmus subspicatus: 169 mg/L
102-71-6	72h EC50 Desmodesmus subspicatus: 216 mg/L
Component	Fish
Triethanolamine 102-71-6	96h LC50 Pimephales promelas: 10600 - 13000 mg/L [flow-through]
	96h LC50 Lepomis macrochirus: 450 - 1000 mg/L [static] 96h LC50 Pimephales promelas: >1000 mg/L [static]
Component	Crustarea

Component	Crustacea
Triethanolamine	24h EC50 Daphnia magna: 1386 mg/L
102-71-6	

#### Persistence and Degradability

No information available.

## **Bioaccumulation**

No information available.

Component	Partition coefficient
Triethanolamine	-2.53
102-71-6	

# Other adverse effects

No information available

## **13. DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Waste Disposal Methods

Contain and dispose of waste according to local regulations.

## Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

# **14. TRANSPORT INFORMATION**

DOT	Not regulated
Proper Shipping Name	Printing Ink
ICAO / IATA / IMDG / IMO	Not Regulated
Proper Shipping Name	Printing Ink

# 15. REGULATORY INFORMATION

## International Inventories

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

# U.S. Federal Regulations

## SARA 313

 Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

 Component
 CAS-No
 Weight %
 SARA 313 - Threshold Values

 Glycol Ether Acrylate
 Trade Secret
 10 - 30
 1.0

The above glycol ether acrylate is considered a reactive chemical in ultraviolet curable inks. Once initiated by a high dose of ultraviolet light, this glycol ether acrylate rapidly polymerizes (i.e. hardens) and becomes part of the ink film. The polymerization process of UV curable inks is measured in milliseconds.

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Component	CAS-No	Weight %
Glycol Ether Acrylate	Trade Secret	10 - 30

## U.S. State Regulations

Component	Massachusetts Right To Know
Titanium dioxide	X
13463-67-7	
Triethanolamine	X
102-71-6	

Component	Minnesota Right To Know
Titanium dioxide 13463-67-7	x
Acrylated Monomer	x
Acrylated Monomer	X
Triethanolamine 102-71-6	x

Component	New Jersey Right To Know		
Titanium dioxide 13463-67-7	X		
Glycol Ether Acrylate	X		
Triethanolamine	Х		

102-71-6				
Component	Pennsylvania Right To Know			
Titanium dioxide 13463-67-7	X			
Glycol Ether Acrylate	X			
Triethanolamine 102-71-6	Х			

#### California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Component	California Prop. 65	
Titanium dioxide	Carcinogen	

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

## <u>Canada</u>

Component	NPRI - National Pollutant Release Inventory
Triethanolamine Part 4 Substance as set out in Section 65 of th	
102-71-6	Substances in Schedule 1 of the Canadian Environmental
	Protection Act, 1999

16. OTHER INFORMATION						
HMIS:	Health 2	Flammability 1	Reactivity 1	Personal Protection X		
Key or legend to abbrevi	ations and acrony	<u>ms used in the safety da</u>	ata sheet			
Legend - Section 8: EXPOS TWA STEL Ceiling	TWA (time-	weighted average) rt Term Exposure Limit)				
ACGIH: (American Conference A1 - Known Human Carcinogen A2 - Suspected Human Carcinog A3 - Animal Carcinogen IARC: (International Agency fo Group 1 - Carcinogenic to Humar Group 2A - Probably Carcinogeni Group 2B - Possibly Carcinogeni NTP: (National Toxicity Program Known - Known Carcinogen Reasonably Anticipated to be a H OSHA: (Occupational Safety & X - Present	en or Research on Cancer) ns ic to Humans c to Humans m) łuman Carcinogen					

#### **Revision Date**

May-30-2015

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# End of MSDS