



Print Date May-30-2015 Revision Date May-30-2015 Revision Number

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier Product code Product name Product category

18151 Halftone Cyan Dense (MTR) 1800 PowerPrint® Plus UV Screen Ink

Other means of identification Synonyms

Recommended use of the chemical and restrictions on useRecommended usePrinting operations

None

## Details of the supplier of the safety data sheet

UNITED STATES Nazdar Company 8501 Hedge Lane Terrace Shawnee, KS 66227 Tel: 1-913-422-1888 Tel: 1-800-677-4657 Fax: 1-913-422-2294 www.nazdar.com UNITED KINGDOM Nazdar Limited Barton Road Heaton Mersey Stockport, England SK4 3EG Tel: +44 161 442 2111

## Emergency telephone number

USA: Chemtrec: 1-800-424-9300 Outside USA: Chemtrec: 1-703-527-3887 24 Hour Emergency Phone Number

## 2. HAZARDS IDENTIFICATION

## **Classification**

Acute toxicity - Oral	Category 4 - (H302)
Skin Corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1B - (H317)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)

#### Label elements



Hazard Statements H302 - Harmful if swallowed H315 - Causes skin irritation

- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H372 Causes damage to organs through prolonged or repeated exposure
- P280 Wear eye protection/ face protection
- P260 Do not breathe dust/fume/gas/mist/vapors/spray

#### Hazards not otherwise classified (HNOC)

May be harmful in contact with skin.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Component	CAS-No	Weight %	Trade Secret	Note
Glycol Ether Acrylate	Trade Secret	30 - 60	*	
Vinyl Functional Monomer	Trade Secret	10 - 30	*	
Acrylated Monomer	Trade Secret	1 - 5	*	
Acrylated Monomer	Trade Secret	1 - 5	*	
Photoinitiator	Trade Secret	1 - 5	*	
Copper Phthalocyanine Compound	Trade Secret	1 - 5	*	
Photoinitiator	Trade Secret	1 - 5	*	
Silicon Dioxide	7631-86-9	1 - 5	*	
1,2,4-Trimethylbenzene (constituent)	95-63-6	< 0.5	*	1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

## 4. FIRST AID MEASURES

## **Description of first aid measures**

General Advice Eye Contact	Show this safety data sheet to the doctor in attendance. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
Ingestion	DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed None under normal use conditions.

#### Indication of any immediate medical attention and special treatment needed

#### **Notes to Physician**

Treat symptomatically.

## **5. FIRE-FIGHTING MEASURES**

## Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Unsuitable Extinguishing Media

No information available.

#### Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions. Hazardous polymerization may take place during a fire due to heat. Closed containers could violently rupture.

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

#### Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

#### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Handling

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

### Conditions for safe storage, including any incompatibilities

StorageKeep at temperatures between 18°-32°C (65°-90°F). Keep containers tightly closed in a dry,<br/>cool and well-ventilated place. Keep container closed when not in use. Keep out of the<br/>reach of children. Protect from direct sunlight. Keep away from open flames, hot surfaces<br/>and sources of ignition.

**Incompatible Products** 

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure limits

Component	OSHA PEL
Silicon Dioxide	TWA: 6 mg/m <sup>3</sup>
7631-86-9	_

#### Appropriate engineering controls

#### Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

## Individual protection measures, such as personal protective equipment

Eye/face Protection	Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.
Skin Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical Physical State Odor	<u>and chemical properties</u> Liquid Mild Sweet Acrylic	Appearance Odor Threshold	Colored Liquid No information available
<u>Property</u> pH Melting point/freezing point Boiling point/Boiling Range Flash Point Evaporation rate	<u>Values</u> > 149 °C / 300 °F > 94 °C / > 201 °F	<u>Remarks • Methoo</u> No data available No data available Pensky Martens Clo No data available	
Flammability Limit in Air Upper flammability limit Lower flammability limit Vapor Pressure Vapor Density Specific Gravity Water Solubility Solubility in other solvents Partition coefficient: n-octanol Autoignition Temperature Decomposition temperature Kinematic viscosity Dynamic viscosity	1.11 /water	No data available No data available	
Explosive Properties Oxidizing Properties	No data available No data available		
Other Information			
Photochemically Reactive Weight Per Gallon (Ibs/gal)	No 9.24		
VOC by weight % (less water) 0-1	VOC by volume % (less water) 0-1	VOC Ibs/gal (less water) 0-1	VOC grams/liter (less water) 9.33

# **10. STABILITY AND REACTIVITY**

Reactivity No information available.

#### Chemical stability

Stable under normal conditions.

#### Possibility of Hazardous Reactions

None under normal processing. Do not store for longer periods at temperatures above 93°C (200°F).

## Conditions to avoid

Temperatures above 93 °C / 200 °F. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

#### Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

## **11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Inhalation	There is no data for this product.
Eye Contact	There is no data for this product.
Skin Contact	There is no data for this product.
Ingestion	There is no data for this product.

Component	Oral LD50
Glycol Ether Acrylate	4660 µL/kg (Rat)
Acrylated Monomer	5 g/kg (Rat)
Acrylated Monomer	5190 µL/kg (Rat)
Silicon Dioxide 7631-86-9	>5000 mg/kg (Rat)
1,2,4-Trimethylbenzene (constituent) 95-63-6	3400 mg/kg (Rat)
Component	LD50 Dermal
Glycol Ether Acrylate	2540 μL/kg (Rabbit)

Glycol Ether Acrylate	2540 µL/kg (Rabbit)
Acrylated Monomer	3600 µL/kg (Rabbit)
Acrylated Monomer	5000 mg/kg (Rabbit)
Silicon Dioxide 7631-86-9	>2000 mg/kg (Rabbit)
1,2,4-Trimethylbenzene (constituent) 95-63-6	>3160 mg/kg (Rabbit)

Component	Inhalation LC50
Silicon Dioxide 7631-86-9	>2.2 mg/L (Rat)1 h
1,2,4-Trimethylbenzene (constituent) 95-63-6	18 g/m³(Rat)4 h

## Information on toxicological effects

#### Symptoms

There is no data for this product.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	There is no data for this product.
Eye damage/irritation	There is no data for this product.
Irritation	There is no data for this product.
Corrosivity	There is no data for this product.

Sensitisation	There is no data for this product.
Mutagenic Effects	There is no data for this product.
Reproductive Effects	There is no data for this product.
STOT - single exposure	There is no data for this product.
STOT - repeated exposure	There is no data for this product.
Chronic Toxicity	There is no data for this product
Aspiration hazard	There is no data for this product.
Carcinogenicity	This product does not contain any carcinogens or potential carcinogens as listed by OSHA,
	IARC or NTP.

## Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS documentATEmix (oral)2,274.00mg/kgATEmix (dermal)4,915.00mg/kg

# **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Silicon Dioxide 7631-86-9	72h EC50 Pseudokirchneriella subcapitata: 440 mg/L
Component	Fish
Copper Phthalocyanine Compound	48h LC50 Oryzias latipes: >100 mg/L [static]
Silicon Dioxide 7631-86-9	96h LC50 Brachydanio rerio: 5000 mg/L [static]
1,2,4-Trimethylbenzene (constituent) 95-63-6	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through]
Component	Crustacea
Silicon Dioxide	48h EC50 Ceriodaphnia dubia: 7600 mg/L

Silicon Dioxide 7631-86-9	48h EC50 Ceriodaphnia dubia: 7600 mg/L
1,2,4-Trimethylbenzene (constituent) 95-63-6	48h EC50 Daphnia magna: 6.14 mg/L

#### Persistence and Degradability

No information available.

## **Bioaccumulation**

No information available.

Component	Partition coefficient
Copper Phthalocyanine Compound	6.6
1,2,4-Trimethylbenzene (constituent) 95-63-6	3.63

## Other adverse effects

No information available

# **13. DISPOSAL CONSIDERATIONS**

## Waste treatment methods

Waste Disposal Methods

Contain and dispose of waste according to local regulations.

Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## **14. TRANSPORT INFORMATION**

DOT	Not regulated
Proper Shipping Name	Printing Ink
ICAO / IATA / IMDG / IMO	Not Regulated
Proper Shipping Name	Printing Ink

# **15. REGULATORY INFORMATION**

## International Inventories

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

## U.S. Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Glycol Ether Acrylate	Trade Secret	30 - 60	1.0

The above glycol ether acrylate is considered a reactive chemical in ultraviolet curable inks. Once initiated by a high dose of ultraviolet light, this glycol ether acrylate rapidly polymerizes (i.e. hardens) and becomes part of the ink film. The polymerization process of UV curable inks is measured in milliseconds.

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Component	CAS-No	Weight %
Glycol Ether Acrylate	Trade Secret	30 - 60

## U.S. State Regulations

Component	Massachusetts Right To Know
Silicon Dioxide 7631-86-9	Х
1,2,4-Trimethylbenzene (constituent) 95-63-6	Х

Component	Minnesota Right To Know
Acrylated Monomer	X
Acrylated Monomer	X
Silicon Dioxide 7631-86-9	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X

Component	New Jersey Right To Know
Glycol Ether Acrylate	X

Copper Phthalocyanine Compound	Х
Silicon Dioxide 7631-86-9	Х
1,2,4-Trimethylbenzene (constituent) 95-63-6	Х

Component	Pennsylvania Right To Know
Glycol Ether Acrylate	X
Copper Phthalocyanine Compound	x
Silicon Dioxide 7631-86-9	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X

## California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

## Canada

No information available	
Component	NPRI - National Pollutant Release Inventory
Copper Phthalocyanine Compound	Part 1, Group A Substance total of the pure element and the equivalent weight of the element contained in any compound, alloy or mixture
1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999

16. OTHER INFORMATION				
HMIS:	Health 2	Flammability 1	Reactivity 1	Personal Protection

## Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION		
TWA	TWA (time-weighted average)	
STEL	STEL (Short Term Exposure Limit)	
Ceiling	Maximum limit value	

ACGIH: (American Conference of Governmental Industrial Hygienists) A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen A3 - Animal Carcinogen IARC: (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans NTP: (National Toxicity Program) Known - Known Carcinogen Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration) X - Present

## **Revision Date**

May-30-2015

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.