

# SAFETY DATA SHEET

Print DateRevision DateRevision NumberMay-30-2015May-30-20151

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code 5554

Product name Dark Peacock Blue

Product category 5500 Series Flat Poster Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Bulling Company
Heaton Mersey

Tel: 1-913-422-1888 Stockport, England SK4 3EG
Tel: 1-800-677-4657 Tel: +44 161 442 2111

Fax: 1-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: 1-800-424-9300 Outside USA: Chemtrec: 1-703-527-3887

24 Hour Emergency Phone Number

## 2. HAZARDS IDENTIFICATION

#### Classification

Serious eye damage/eye irritation	Category 2 - (H319)
Aspiration toxicity	Category 1 - (H304)
Flammable liquids	Category 3 - (H226)

#### Label elements







Signal Word Danger

#### **Hazard Statements**

H304 - May be fatal if swallowed and enters airways

H319 - Causes serious eye irritation H226 - Flammable liquid and vapor

P331 - Do NOT induce vomiting

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

#### Hazards not otherwise classified (HNOC)

May be harmful in contact with skin.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Component	CAS-No	Weight %	Trade Secret	Note
Talc	14807-96-6	10 - 30	*	
Stoddard solvent	8052-41-3	10 - 30	*	
Petroleum naphtha, light aromatic	64742-95-6	10 - 30	*	
Titanium dioxide	13463-67-7	5 - 10	*	
1,2,4-Trimethylbenzene (constituent)	95-63-6	5 - 10	*	1
Ethylene glycol monopropyl ether	2807-30-9	1 - 5	*	
Ethyl alcohol	64-17-5	1 - 5	*	
Copper Phthalocyanine Compound	Trade Secret	1 - 5	*	
Calcium Carbonate	1317-65-3	1 - 5	*	
1,3,5-Trimethylbenzene (constituent)	108-67-8	1 - 5	*	1
Cumene (constituent)	98-82-8	< 1	*	1
Crystalline silica (cristobalite)	14464-46-1	< 0.5	*	

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

## 4. FIRST AID MEASURES

#### **Description of first aid measures**

**General Advice** Show this safety data sheet to the doctor in attendance.

**Eye Contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

**Skin Contact** Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

**Inhalation** Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

**Ingestion** DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

## Most important symptoms and effects, both acute and delayed

None under normal use conditions.

## Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

## **Suitable Extinguishing Media**

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### **Unsuitable Extinguishing Media**

No information available.

#### **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

## 6. ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

#### **Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling**Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

#### Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

open flames, hot surfaces and sources of ignition. Keep container closed when not in use.

Keep out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

### **Exposure limits**

Component	ACGIH TLV	
Talc 14807-96-6	TWA: 2 mg/m³ (particulate matter)	
Stoddard solvent 8052-41-3	TWA: 100 ppm	
Titanium dioxide 13463-67-7	TWA: 10 mg/m³	
Ethyl alcohol 64-17-5	STEL: 1000 ppm	
Cumene (constituent) 98-82-8	TWA: 50 ppm	
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.025 mg/m³ (respirable fraction)	

Component	OSHA PEL
Talc 14807-96-6	TWA: 2 mg/m³ (respirable dust)
Stoddard solvent	TWA: 100 ppm
8052-41-3	TWA: 525 mg/m <sup>3</sup>

	TWA: 500 ppm TWA: 2900 mg/m³
Titanium dioxide 13463-67-7	TWA: 10 mg/m³ (total dust) TWA: 15 mg/m³ (total dust)
Ethyl alcohol 64-17-5	TWA: 1000 ppm TWA: 1900 mg/m³
Calcium Carbonate 1317-65-3	TWA: 15 mg/m³ (total dust) TWA: 5 mg/m³ (respirable fraction)
Cumene (constituent) 98-82-8	TWA: 50 ppm TWA: 245 mg/m³ Skin
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.05 mg/m³ (respirable dust)

Component	Ontario TWAEV
Talc 14807-96-6	TWA: 2 mg/m³ (respirable)
Stoddard solvent 8052-41-3	TWA: 525 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	TWA: 10 mg/m³ (total dust)
Ethylene glycol monopropyl ether 2807-30-9	TWA: 25 ppm TWA: 110 mg/m³ Skin
Ethyl alcohol 64-17-5	STEL: 1000 ppm
Cumene (constituent) 98-82-8	TWA: 50 ppm
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.05 mg/m³ (respirable)

Component	Mexico OEL (TWA)
Talc 14807-96-6	TWA/LMPE-PPT: 2 mg/m³ (respirable fraction)
Stoddard solvent 8052-41-3	TWA/LMPE-PPT: 100 ppm TWA/LMPE-PPT: 523 mg/m³ STEL/LMPE-CT: 200 ppm STEL/LMPE-CT: 1050 mg/m³
Titanium dioxide 13463-67-7	TWA/LMPE-PPT: 10 mg/m³ (as Ti) STEL/LMPE-CT: 20 mg/m³ (as Ti)
Ethyl alcohol 64-17-5	TWA/LMPE-PPT: 1000 ppm TWA/LMPE-PPT: 1900 mg/m³
Calcium Carbonate 1317-65-3	TWA/LMPE-PPT: 10 mg/m³ STEL/LMPE-CT: 20 mg/m³
Cumene (constituent) 98-82-8	TWA/LMPE-PPT: 50 ppm TWA/LMPE-PPT: 245 mg/m³ STEL/LMPE-CT: 75 ppm STEL/LMPE-CT: 365 mg/m³
Crystalline silica (cristobalite) 14464-46-1	TWA/LMPE-PPT: 0.05 mg/m³ (respirable fraction)

## **Appropriate engineering controls**

### **Engineering Measures**

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

## Individual protection measures, such as personal protective equipment

**Eye/face Protection** Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

**Skin Protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in

accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid Appearance Colored Liquid

Odor Characteristic Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

No data available

Melting point/freezing point

No data available

Boiling point/Boiling Range > 149 °C / 300 °F

Flash Point 29 °C / 85 °F Pensky Martens Closed Cup (PMCC)

Evaporation rate No data available

Flammability Limit in Air

Upper flammability limit

Lower flammability limit

No data available

No data available

Vapor Pressure

No data available

Vapor PressureNo data availableVapor DensityNo data available

Specific Gravity 1.19

Water SolubilityNo data availableSolubility in other solventsNo data availablePartition coefficient: n-octanol/waterNo data availableAutoignition TemperatureNo data availableDecomposition temperatureNo data available

Autoignition TemperatureNo data availableDecomposition temperatureNo data availableKinematic viscosityNo data availableDynamic viscosityNo data available

Explosive Properties No data available Oxidizing Properties No data available

Other Information

Photochemically Reactive Yes Weight Per Gallon (lbs/gal) 9.9

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
47.14	68.15	4.67	559.79

## 10. STABILITY AND REACTIVITY

### Reactivity

No information available.

## **Chemical stability**

Stable under normal conditions.

## Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Revision Date May-30-2015

#### 5554 - Dark Peacock Blue

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

## **Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

InhalationThere is no data for this product.Eye ContactThere is no data for this product.Skin ContactThere is no data for this product.IngestionThere is no data for this product.

Component	Oral LD50
Petroleum naphtha, light aromatic 64742-95-6	8400 mg/kg(Rat)
Titanium dioxide 13463-67-7	>10000 mg/kg(Rat)
1,2,4-Trimethylbenzene (constituent) 95-63-6	3400 mg/kg(Rat)
Ethylene glycol monopropyl ether 2807-30-9	3089 mg/kg(Rat)
Ethyl alcohol 64-17-5	7060 mg/kg(Rat)
1,3,5-Trimethylbenzene (constituent) 108-67-8	5000 mg/kg(Rat)
Cumene (constituent) 98-82-8	1400 mg/kg(Rat)

Component	LD50 Dermal
Petroleum naphtha, light aromatic 64742-95-6	>2000 mg/kg(Rabbit)
1,2,4-Trimethylbenzene (constituent) 95-63-6	>3160 mg/kg(Rabbit)
Ethylene glycol monopropyl ether 2807-30-9	960 μL/kg (Rabbit)
Cumene (constituent) 98-82-8	>3160 mg/kg(Rabbit)

Component	Inhalation LC50
Petroleum naphtha, light aromatic 64742-95-6	3400 ppm (Rat) 4 h >5.2 mg/L (Rat) 4 h
1,2,4-Trimethylbenzene (constituent) 95-63-6	18 g/m³(Rat ) 4 h
Ethyl alcohol 64-17-5	124.7 mg/L (Rat)4 h
1,3,5-Trimethylbenzene (constituent) 108-67-8	24 g/m³(Rat ) 4 h
Cumene (constituent) 98-82-8	39000 mg/m³ ( Rat ) 4 h

## Information on toxicological effects

**Symptoms** There is no data for this product.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationThere is no data for this product.Eye damage/irritationThere is no data for this product.IrritationThere is no data for this product.CorrosivityThere is no data for this product.SensitisationThere is no data for this product.Mutagenic EffectsThere is no data for this product.

D---- 0.1

Reproductive Effects
STOT - single exposure
STOT - repeated exposure
Chronic Toxicity
Aspiration hazard
There is no data for this product.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	IARC
Titanium dioxide 13463-67-7	Group 2B
Cumene (constituent) 98-82-8	Group 2B
Crystalline silica (cristobalite) 14464-46-1	Group 1

Component	OSHA
Titanium dioxide	X
13463-67-7	
Cumene (constituent)	X
98-82-8	
Crystalline silica (cristobalite)	X
14464-46-1	

## Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 15,639.00 mg/kg
ATEmix (dermal) 7,949.00 mg/kg
ATEmix (inhalation-dust/mist) 34.50 mg/l
ATEmix (inhalation-vapor) 1,627.00 mg/l

## 12. ECOLOGICAL INFORMATION

## **Ecotoxicity**

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Cumene (constituent)	72h EC50 Pseudokirchneriella subcapitata: 2.6 mg/L
98-82-8	

Component	Fish
Talc 14807-96-6	96h LC50 Brachydanio rerio: >100 g/L [semi-static]
Petroleum naphtha, light aromatic 64742-95-6	96h LC50 Oncorhynchus mykiss: 9.22 mg/L
1,2,4-Trimethylbenzene (constituent) 95-63-6	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through]
Ethyl alcohol 64-17-5	96h LC50 Oncorhynchus mykiss: 12.0 - 16.0 mL/L [static] 96h LC50 Pimephales promelas: 13400 - 15100 mg/L [flow-through] 96h LC50 Pimephales promelas: >100 mg/L [static]
Copper Phthalocyanine Compound	48h LC50 Oryzias latipes: >100 mg/L [static]
1,3,5-Trimethylbenzene (constituent) 108-67-8	96h LC50 Pimephales promelas: 3.48 mg/L
Cumene (constituent) 98-82-8	96h LC50 Pimephales promelas: 6.04 - 6.61 mg/L [flow-through] 96h LC50 Oncorhynchus mykiss: 2.7 mg/L [semi-static] 96h LC50 Oncorhynchus mykiss: 4.8 mg/L [flow-through] 96h LC50 Poecilia reticulata: 5.1 mg/L [semi-static]

Component	Crustacea	
1,2,4-Trimethylbenzene (constituent)	48h EC50 Daphnia magna: 6.14 mg/L	
95-63-6		
Ethyl alcohol	48h LC50 Daphnia magna: 9268 - 14221 mg/L	
64-17-5	24h EC50 Daphnia magna: 10800 mg/L	
1,3,5-Trimethylbenzene (constituent)	24h EC50 Daphnia magna: 50 mg/L	
108-67-8		
Cumene (constituent)	48h EC50 Daphnia magna: 7.9 - 14.1 mg/L [static]	
98-82-8	48h EC50 Daphnia magna: 0.6 mg/L	

#### Persistence and Degradability

No information available.

#### **Bioaccumulation**

No information available.

Component	Partition coefficient
1,2,4-Trimethylbenzene (constituent) 95-63-6	3.63
Ethyl alcohol 64-17-5	-0.32
Copper Phthalocyanine Compound	6.6
Cumene (constituent) 98-82-8	3.55

#### Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Waste Disposal Methods** Contain and dispose of waste according to local regulations.

**Contaminated Packaging** Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1210 Printing Ink **Proper Shipping Name** 

**Hazard Class** 3 **Packing Group** Ш

ICAO / IATA / IMDG / IMO

UN/ID no. UN1210 **Proper Shipping Name** Printing Ink

**Hazard Class** 3 **Packing Group** Ш

## 15. REGULATORY INFORMATION

## **International Inventories**

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

## U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical

or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
1,2,4-Trimethylbenzene (constituent)	95-63-6	5 - 10	1.0
Ethylene glycol monopropyl ether	2807-30-9	1 - 5	1.0

<u>Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)</u>
This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air

Component	CAS-No	Weight %
Ethylene glycol monopropyl ether	2807-30-9	1 - 5

## **U.S. State Regulations**

Component	Massachusetts Right To Know
Talc 14807-96-6	Х
Stoddard solvent 8052-41-3	Х
Titanium dioxide 13463-67-7	Х
1,2,4-Trimethylbenzene (constituent) 95-63-6	Х
Ethyl alcohol 64-17-5	Х
Calcium Carbonate 1317-65-3	Х
1,3,5-Trimethylbenzene (constituent) 108-67-8	Х
Cumene (constituent) 98-82-8	Х
Crystalline silica (cristobalite) 14464-46-1	X

Component	Minnesota Right To Know
Talc	X
14807-96-6	
Stoddard solvent	X
8052-41-3	
Titanium dioxide	X
13463-67-7	
1,2,4-Trimethylbenzene (constituent)	X
95-63-6	
Ethyl alcohol	X
64-17-5	
Calcium Carbonate	X
1317-65-3	
Cumene (constituent)	X
98-82-8	
Crystalline silica (cristobalite)	X
14464-46-1	

Component	New Jersey Right To Know
Talc 14807-96-6	X
Stoddard solvent 8052-41-3	Х
Titanium dioxide 13463-67-7	Х
1,2,4-Trimethylbenzene (constituent) 95-63-6	Х
Ethylene glycol monopropyl ether 2807-30-9	X
Ethyl alcohol	X

64-17-5	
Copper Phthalocyanine Compound	X
Calcium Carbonate 1317-65-3	X
Cumene (constituent) 98-82-8	X
Crystalline silica (cristobalite) 14464-46-1	X

Component	Pennsylvania Right To Know
Talc 14807-96-6	X
Stoddard solvent 8052-41-3	X
Titanium dioxide 13463-67-7	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Ethylene glycol monopropyl ether 2807-30-9	X
Ethyl alcohol 64-17-5	X
Copper Phthalocyanine Compound	X
Calcium Carbonate 1317-65-3	X
Cumene (constituent) 98-82-8	X
Crystalline silica (cristobalite) 14464-46-1	X

<u>California Prop. 65</u>
This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Commonant Colifornia Draw CF		California Bron CE
- 1	Component	California Prop. 65
	Titanium dioxide	Carcinogen
ı	Cumene (constituent)	Carcinogen

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

## **Canada**

Component	NPRI - National Pollutant Release Inventory
Stoddard solvent 8052-41-3	Part 5, Other Groups and Mixtures
Petroleum naphtha, light aromatic 64742-95-6	Part 5, Other Groups and Mixtures
1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Ethylene glycol monopropyl ether 2807-30-9	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Ethyl alcohol 64-17-5	Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Copper Phthalocyanine Compound	Part 1, Group A Substance total of the pure element and the equivalent weight of the element contained in any compound, alloy or mixture
1,3,5-Trimethylbenzene (constituent) 108-67-8	Part 5, Isomer Groups total of 1,2,3-Trimethylbenzene, CAS No. 526-73-8, and 1,3,5-Trimethylbenzene, CAS No. 108-67-8, except 1,2,4-Trimethylbenzene, CAS No. 95-63-6 Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999

5554 - Dark Peacock Blue Revision Date May-30-2015

Cumene (constituent)	Part 1, Group A Substance Part 4 Substance as set out in Section
98-82-8	65 of the List of Toxic Substances in Schedule 1 of the Canadian
	Environmental Protection Act, 1999

## **16. OTHER INFORMATION**

HMIS:HealthFlammabilityReactivityPersonal Protection2 \*30X

## Key or legend to abbreviations and acronyms used in the safety data sheet

## Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

#### ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen
OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date May-30-2015

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of MSDS**