

# SAFETY DATA SHEET

Print DateRevision DateRevision NumberMay-30-2015May-30-20151

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code 5547

Product name Dark Royal Purple

Product category 5500 Series Flat Poster Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Burton Road
Heaton Mersey

Tel: 1-913-422-1888 Stockport, England SK4 3EG
Tel: 1-800-677-4657 Tel: +44 161 442 2111

Fax: 1-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: 1-800-424-9300

Outside USA: Chemtrec: 1-703-527-3887 24 Hour Emergency Phone Number

# 2. HAZARDS IDENTIFICATION

#### Classification

| Serious eye damage/eye irritation | Category 2 - (H319) |
|-----------------------------------|---------------------|
| Aspiration toxicity               | Category 1 - (H304) |
| Flammable liquids                 | Category 3 - (H226) |

#### Label elements







#### Signal Word Danger

#### **Hazard Statements**

H304 - May be fatal if swallowed and enters airways

H319 - Causes serious eye irritation H226 - Flammable liquid and vapor

P331 - Do NOT induce vomiting

\_\_\_\_\_

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

#### Hazards not otherwise classified (HNOC)

May be harmful in contact with skin.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

| Component                            | CAS-No       | Weight % | Trade<br>Secret | Note |
|--------------------------------------|--------------|----------|-----------------|------|
| Stoddard solvent                     | 8052-41-3    | 10 - 30  | *               |      |
| Petroleum naphtha, light aromatic    | 64742-95-6   | 10 - 30  | *               |      |
| Crystalline silica (cristobalite)    | 14464-46-1   | 5 - 10   | *               |      |
| 1,2,4-Trimethylbenzene (constituent) | 95-63-6      | 5 - 10   | *               | 1    |
| Talc                                 | 14807-96-6   | 5 - 10   | *               |      |
| Inert Pigment                        | Trade Secret | 5 - 10   | *               |      |
| Ethylene glycol monopropyl ether     | 2807-30-9    | 1 - 5    | *               |      |
| Titanium dioxide                     | 13463-67-7   | 1 - 5    | *               |      |
| 1,3,5-Trimethylbenzene (constituent) | 108-67-8     | 1 - 5    | *               | 1    |
| Xylenes (o-, m-, p- isomers)         | 1330-20-7    | 1 - 5    | *               |      |
| Cumene (constituent)                 | 98-82-8      | < 1      | *               | 1    |
| Quartz, crystalline silica           | 14808-60-7   | < 0.5    | *               |      |
| Ethyl benzene (constituent)          | 100-41-4     | < 0.5    | *               | 1    |

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

# 4. FIRST AID MEASURES

#### Description of first aid measures

**General Advice** Show this safety data sheet to the doctor in attendance.

**Eye Contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

**Skin Contact** Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

**Inhalation** Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

Ingestion DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

#### Most important symptoms and effects, both acute and delayed

None under normal use conditions.

# Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

# Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

# **Unsuitable Extinguishing Media**

No information available.

Revision Date May-30-2015

#### **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

#### Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

# Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

# 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

#### Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

open flames, hot surfaces and sources of ignition. Keep container closed when not in use.

Keep out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### **Exposure limits**

| Component                                       | ACGIH TLV                              |
|---|--|
| Stoddard solvent<br>8052-41-3                   | TWA: 100 ppm                           |
| Crystalline silica (cristobalite)<br>14464-46-1 | TWA: 0.025 mg/m³ (respirable fraction) |
| Talc<br>14807-96-6                              | TWA: 2 mg/m³ (particulate matter)      |
| Titanium dioxide<br>13463-67-7                  | TWA: 10 mg/m³                          |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | TWA: 100 ppm<br>STEL: 150 ppm          |
| Cumene (constituent)<br>98-82-8                 | TWA: 50 ppm                            |
| Quartz, crystalline silica<br>14808-60-7        | TWA: 0.025 mg/m³ (respirable fraction) |
| Ethyl benzene (constituent)<br>100-41-4         | TWA: 20 ppm                            |

# 5547 - Dark Royal Purple

| Component                         | OSHA PEL                          |
|-----------------------------------|-----------------------------------|
| Stoddard solvent                  | TWA: 100 ppm                      |
| 8052-41-3                         | TWA: 525 mg/m <sup>3</sup>        |
|                                   | TWA: 500 ppm                      |
|                                   | TWA: 2900 mg/m <sup>3</sup>       |
| Crystalline silica (cristobalite) | TWA: 0.05 mg/m³ (respirable dust) |
| 14464-46-1                        |                                   |
| Talc                              | TWA: 2 mg/m³ (respirable dust)    |
| 14807-96-6                        |                                   |
| Titanium dioxide                  | TWA: 10 mg/m³ (total dust)        |
| 13463-67-7                        | TWA: 15 mg/m³ (total dust)        |
| Xylenes (o-, m-, p- isomers)      | TWA: 100 ppm                      |
| 1330-20-7                         | TWA: 435 mg/m <sup>3</sup>        |
|                                   | STEL: 150 ppm                     |
|                                   | STEL: 655 mg/m <sup>3</sup>       |
| Cumene (constituent)              | TWA: 50 ppm                       |
| 98-82-8                           | TWA: 245 mg/m <sup>3</sup>        |
|                                   | Skin                              |
| Quartz, crystalline silica        | TWA: 0.1 mg/m³ (respirable dust)  |
| 14808-60-7                        |                                   |
| Ethyl benzene (constituent)       | TWA: 100 ppm                      |
| 100-41-4                          | TWA: 435 mg/m <sup>3</sup>        |
|                                   | STEL: 125 ppm                     |
|                                   | STEL: 545 mg/m <sup>3</sup>       |

| omponent Ontario TWAEV                          |                                       |
|---|---------------------------------------|
| Stoddard solvent<br>8052-41-3                   | TWA: 525 mg/m <sup>3</sup>            |
| Crystalline silica (cristobalite)<br>14464-46-1 | TWA: 0.05 mg/m³ (respirable)          |
| Talc<br>14807-96-6                              | TWA: 2 mg/m³ (respirable)             |
| Ethylene glycol monopropyl ether 2807-30-9      | TWA: 25 ppm<br>TWA: 110 mg/m³<br>Skin |
| Titanium dioxide<br>13463-67-7                  | TWA: 10 mg/m³ (total dust)            |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | TWA: 100 ppm<br>STEL: 150 ppm         |
| Cumene (constituent)<br>98-82-8                 | TWA: 50 ppm                           |
| Quartz, crystalline silica<br>14808-60-7        | TWA: 0.10 mg/m³ (respirable)          |
| Ethyl benzene (constituent)<br>100-41-4         | TWA: 100 ppm<br>STEL: 125 ppm         |

| Component                                       | Mexico OEL (TWA)  |
|---|---|
| Stoddard solvent<br>8052-41-3                   | TWA/LMPE-PPT: 100 ppm<br>TWA/LMPE-PPT: 523 mg/m³<br>STEL/LMPE-CT: 200 ppm<br>STEL/LMPE-CT: 1050 mg/m³ |
| Crystalline silica (cristobalite)<br>14464-46-1 | TWA/LMPE-PPT: 0.05 mg/m³ (respirable fraction)  |
| Talc<br>14807-96-6                              | TWA/LMPE-PPT: 2 mg/m³ (respirable fraction)   |
| Titanium dioxide<br>13463-67-7                  | TWA/LMPE-PPT: 10 mg/m³ (as Ti)<br>STEL/LMPE-CT: 20 mg/m³ (as Ti)                                      |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | TWA/LMPE-PPT: 100 ppm TWA/LMPE-PPT: 435 mg/m³ STEL/LMPE-CT: 150 ppm STEL/LMPE-CT: 655 mg/m³           |
| Cumene (constituent)<br>98-82-8                 | TWA/LMPE-PPT: 50 ppm TWA/LMPE-PPT: 245 mg/m³ STEL/LMPE-CT: 75 ppm STEL/LMPE-CT: 365 mg/m³             |
| Quartz, crystalline silica<br>14808-60-7        | TWA/LMPE-PPT: 0.1 mg/m³ (respirable fraction)   |

|  | 1 |  |  |
|--|---|--|--|

 Ethyl benzene (constituent)
 TWA/LMPE-PPT: 100 ppm

 100-41-4
 TWA/LMPE-PT: 435 mg/m³

 STEL/LMPE-CT: 125 ppm
 STEL/LMPE-CT: 545 mg/m³

#### **Appropriate engineering controls**

Engineering Measures Provide a good standard of general ventilation. Natural ventilation is from doors, windows

etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In

case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

**Eye/face Protection** Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

**Skin Protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in

accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid Appearance Colored Liquid

Odor Characteristic Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No data available
Melting point/freezing point No data available

Melting point/freezing point No data available

Boiling point/Boiling Range > 149 °C / 300 °F

Flash Point 29 °C / 85 °F Pensky Martens Closed Cup (PMCC)

Evaporation rate No data available

Flammability Limit in Air

Unper flammability limit

Upper flammability limit

Lower flammability limit

No data available

No data available

Vapor Pressure
No data available
Vapor Density
No data available

Specific Gravity 1.07

Water SolubilityNo data availableSolubility in other solventsNo data availablePartition coefficient: n-octanol/waterNo data available

Autoignition TemperatureNo data availableDecomposition temperatureNo data availableKinematic viscosityNo data available

No data available

Dynamic viscosity

No data available

Explosive Properties

No data available

Other Information

**Oxidizing Properties** 

Photochemically Reactive Yes Weight Per Gallon (lbs/gal) 8.88

| VOC by weight % | VOC by volume % | VOC lbs/gal  | VOC grams/liter |
|-----------------|-----------------|--------------|-----------------|
| (less water)    | (less water)    | (less water) | (less water)    |
| 46.71           | 57.13           | 4.15         | 497.59          |

# 10. STABILITY AND REACTIVITY

#### Reactivity

No information available.

#### Chemical stability

Stable under normal conditions.

#### Possibility of Hazardous Reactions

None under normal processing.

# Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

#### **Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

InhalationThere is no data for this product.Eye ContactThere is no data for this product.Skin ContactThere is no data for this product.IngestionThere is no data for this product.

| Component  | Oral LD50         |
|--|-------------------|
| Petroleum naphtha, light aromatic 64742-95-6     | 8400 mg/kg (Rat)  |
| 1,2,4-Trimethylbenzene (constituent)<br>95-63-6  | 3400 mg/kg (Rat)  |
| Ethylene glycol monopropyl ether 2807-30-9       | 3089 mg/kg (Rat)  |
| Titanium dioxide<br>13463-67-7                   | >10000 mg/kg(Rat) |
| 1,3,5-Trimethylbenzene (constituent)<br>108-67-8 | 5000 mg/kg (Rat)  |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7        | 4300 mg/kg (Rat)  |
| Cumene (constituent)<br>98-82-8                  | 1400 mg/kg (Rat)  |
| Quartz, crystalline silica<br>14808-60-7         | 500 mg/kg(Rat)    |
| Ethyl benzene (constituent)<br>100-41-4          | 3500 mg/kg (Rat)  |

| Component                                       | LD50 Dermal            |
|---|------------------------|
| Petroleum naphtha, light aromatic 64742-95-6    | >2000 mg/kg(Rabbit)    |
| 1,2,4-Trimethylbenzene (constituent)<br>95-63-6 | >3160 mg/kg ( Rabbit ) |
| Ethylene glycol monopropyl ether 2807-30-9      | 960 μL/kg(Rabbit)      |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | >1700 mg/kg(Rabbit)    |
| Cumene (constituent)                            | >3160 mg/kg(Rabbit)    |

| 98-82-8                     |                      |
|-----------------------------|----------------------|
| Ethyl benzene (constituent) | 15354 mg/kg (Rabbit) |
| 100-41-4                    |                      |

| Component  | Inhalation LC50                           |
|--|---|
| Petroleum naphtha, light aromatic 64742-95-6     | 3400 ppm (Rat) 4 h<br>>5.2 mg/L (Rat) 4 h |
| 1,2,4-Trimethylbenzene (constituent)<br>95-63-6  | 18 g/m³(Rat ) 4 h                         |
| 1,3,5-Trimethylbenzene (constituent)<br>108-67-8 | 24 g/m³(Rat ) 4 h                         |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7        | 5000 ppm (Rat)4 h<br>47635 mg/L (Rat)4 h  |
| Cumene (constituent)<br>98-82-8                  | 39000 mg/m³ (Rat) 4 h                     |
| Ethyl benzene (constituent)<br>100-41-4          | 17.2 mg/L (Rat)4 h                        |

# Information on toxicological effects

**Symptoms** There is no data for this product.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation There is no data for this product. Eye damage/irritation There is no data for this product. Irritation There is no data for this product. There is no data for this product. Corrosivity Sensitisation There is no data for this product. **Mutagenic Effects** There is no data for this product. **Reproductive Effects** There is no data for this product. STOT - single exposure There is no data for this product. There is no data for this product. STOT - repeated exposure **Chronic Toxicity** There is no data for this product **Aspiration hazard** There is no data for this product.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

|                             | tanded to the first time to the transfer and the first time to the time time great time to the time time great |
|-----------------------------|--|
| Component                   | ACGIH  |
| Ethyl benzene (constituent) | A3   |
| 100-41-4                    |  |

| Component                                       | IARC     |
|---|----------|
| Crystalline silica (cristobalite)<br>14464-46-1 | Group 1  |
| Titanium dioxide<br>13463-67-7                  | Group 2B |
| Cumene (constituent)<br>98-82-8                 | Group 2B |
| Quartz, crystalline silica<br>14808-60-7        | Group 1  |
| Ethyl benzene (constituent)<br>100-41-4         | Group 2B |

| Component                  | NTP   |
|----------------------------|-------|
| Quartz, crystalline silica | Known |
| 14808-60-7                 |       |

| Component                                       | OSHA |
|---|------|
| Crystalline silica (cristobalite)<br>14464-46-1 | X    |
| Titanium dioxide 13463-67-7                     | X    |
| Cumene (constituent)<br>98-82-8                 | X    |
| Quartz, crystalline silica<br>14808-60-7        | X    |
| Ethyl benzene (constituent)                     | X    |

| 100-41-4 |  |
|----------|--|

# Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 20,693.00 mg/kg
ATEmix (dermal) 6,944.00 mg/kg
ATEmix (inhalation-dust/mist) 25.80 mg/l
ATEmix (inhalation-vapor) 837.00 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Component                               | Algae/aquatic plants  |
|---|---|
| Cumene (constituent)<br>98-82-8         | 72h EC50 Pseudokirchneriella subcapitata: 2.6 mg/L  |
| Ethyl benzene (constituent)<br>100-41-4 | 96h EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static] 72h EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L [static] 72h EC50 Pseudokirchneriella subcapitata: 4.6 mg/L 96h EC50 Pseudokirchneriella subcapitata: >438 mg/L |

| Component  | Fish   |
|--|--|
| Petroleum naphtha, light aromatic 64742-95-6     | 96h LC50 Oncorhynchus mykiss: 9.22 mg/L  |
| 1,2,4-Trimethylbenzene (constituent)<br>95-63-6  | 96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through]  |
| Talc<br>14807-96-6                               | 96h LC50 Brachydanio rerio: >100 g/L [semi-static]   |
| 1,3,5-Trimethylbenzene (constituent)<br>108-67-8 | 96h LC50 Pimephales promelas: 3.48 mg/L  |
| Cumene (constituent)<br>98-82-8                  | 96h LC50 Pimephales promelas: 6.04 - 6.61 mg/L [flow-through] 96h LC50 Oncorhynchus mykiss: 2.7 mg/L [semi-static] 96h LC50 Oncorhynchus mykiss: 4.8 mg/L [flow-through] 96h LC50 Poecilia reticulata: 5.1 mg/L [semi-static]  |
| Ethyl benzene (constituent)<br>100-41-4          | 96h LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static] 96h LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through] 96h LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static] 96h LC50 Lepomis macrochirus: 32 mg/L [static] 96h LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static] 96h LC50 Poecilia reticulata: 9.6 mg/L [static] |

| Component  | Crustacea  |  |
|--|--|--|
| 1,2,4-Trimethylbenzene (constituent)             | 48h EC50 Daphnia magna: 6.14 mg/L  |  |
| 95-63-6  |  |  |
| 1,3,5-Trimethylbenzene (constituent)<br>108-67-8 | 24h EC50 Daphnia magna: 50 mg/L  |  |
| Cumene (constituent)<br>98-82-8                  | 48h EC50 Daphnia magna: 7.9 - 14.1 mg/L [static]<br>48h EC50 Daphnia magna: 0.6 mg/L |  |
| Ethyl benzene (constituent)<br>100-41-4          | 48h EC50 Daphnia magna: 1.8 - 2.4 mg/L   |  |

#### Persistence and Degradability

No information available.

# **Bioaccumulation**

No information available.

| Component                            | Partition coefficient |
|--------------------------------------|-----------------------|
| 1,2,4-Trimethylbenzene (constituent) | 3.63                  |

95-63-6

Xylenes (o-, m-, p- isomers)
1330-20-7

Cumene (constituent)
98-82-8

Ethyl benzene (constituent)
100-41-4

3.118

#### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. TRANSPORT INFORMATION

DOT

UN1210 Proper Shipping Name UN1210 Printing Ink

Hazard Class 3
Packing Group III

ICAO / IATA / IMDG / IMO

UN/ID no. UN1210
Proper Shipping Name Printing Ink

Hazard Class 3
Packing Group III

# 15. REGULATORY INFORMATION

# **International Inventories**

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

# U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations. Part 372.

| Component                            | CAS-No    | Weight % | SARA 313 - Threshold<br>Values |
|--------------------------------------|-----------|----------|--------------------------------|
| 1,2,4-Trimethylbenzene (constituent) | 95-63-6   | 5 - 10   | 1.0                            |
| Ethylene glycol monopropyl ether     | 2807-30-9 | 1 - 5    | 1.0                            |
| Xylenes (o-, m-, p- isomers)         | 1330-20-7 | 1 - 5    | 1.0                            |
| Ethyl benzene (constituent)          | 100-41-4  | < 0.5    | 0.1                            |

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

| Component                        | CAS-No    | Weight % |
|----------------------------------|-----------|----------|
| Ethylene glycol monopropyl ether | 2807-30-9 | 1 - 5    |
| Xylenes (o-, m-, p- isomers)     | 1330-20-7 | 1 - 5    |

# U.S. State Regulations

# 5547 - Dark Royal Purple

| Component  | Massachusetts<br>Right To Know |
|--|--------------------------------|
| Stoddard solvent<br>8052-41-3                    | X                              |
| Crystalline silica (cristobalite)<br>14464-46-1  | X                              |
| 1,2,4-Trimethylbenzene (constituent)<br>95-63-6  | X                              |
| Talc<br>14807-96-6                               | X                              |
| Titanium dioxide<br>13463-67-7                   | X                              |
| 1,3,5-Trimethylbenzene (constituent)<br>108-67-8 | X                              |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7        | X                              |
| Cumene (constituent)<br>98-82-8                  | X                              |
| Quartz, crystalline silica<br>14808-60-7         | X                              |
| Ethyl benzene (constituent)<br>100-41-4          | X                              |

| Component                                       | Minnesota<br>Right To Know |
|---|----------------------------|
| Stoddard solvent<br>8052-41-3                   | X                          |
| Crystalline silica (cristobalite)<br>14464-46-1 | Х                          |
| 1,2,4-Trimethylbenzene (constituent)<br>95-63-6 | Х                          |
| Talc<br>14807-96-6                              | Х                          |
| Titanium dioxide<br>13463-67-7                  | Х                          |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | X                          |
| Cumene (constituent)<br>98-82-8                 | Х                          |
| Quartz, crystalline silica<br>14808-60-7        | X                          |
| Ethyl benzene (constituent)<br>100-41-4         | X                          |

| Component                                       | New Jersey<br>Right To Know |
|---|-----------------------------|
| Stoddard solvent<br>8052-41-3                   | X                           |
| Crystalline silica (cristobalite)<br>14464-46-1 | X                           |
| 1,2,4-Trimethylbenzene (constituent)<br>95-63-6 | X                           |
| Talc<br>14807-96-6                              | X                           |
| Ethylene glycol monopropyl ether 2807-30-9      | X                           |
| Titanium dioxide<br>13463-67-7                  | X                           |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | X                           |
| Cumene (constituent)<br>98-82-8                 | X                           |
| Quartz, crystalline silica<br>14808-60-7        | X                           |
| Ethyl benzene (constituent)<br>100-41-4         | X                           |

| Component | Pennsylvania |
|-----------|--------------|
|           |              |

|   | Right To Know |
|---|---------------|
| Stoddard solvent<br>8052-41-3                   | Х             |
| Crystalline silica (cristobalite)<br>14464-46-1 | Х             |
| 1,2,4-Trimethylbenzene (constituent)<br>95-63-6 | Х             |
| Talc<br>14807-96-6                              | Х             |
| Inert Pigment                                   | Х             |
| Ethylene glycol monopropyl ether 2807-30-9      | Х             |
| Titanium dioxide<br>13463-67-7                  | Х             |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | X             |
| Cumene (constituent)<br>98-82-8                 | Х             |
| Quartz, crystalline silica<br>14808-60-7        | Х             |
| Ethyl benzene (constituent)<br>100-41-4         | Х             |

# California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other

reproductive harm

| Component                   | California Prop. 65 |
|-----------------------------|---------------------|
| Titanium dioxide            | Carcinogen          |
| Cumene (constituent)        | Carcinogen          |
| Quartz, crystalline silica  | Carcinogen          |
| Ethyl benzene (constituent) | Carcinogen          |

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product

# **Canada**

| Component  | NPRI - National Pollutant Release Inventory  |
|--|--|
| Stoddard solvent<br>8052-41-3                    | Part 5, Other Groups and Mixtures  |
| Petroleum naphtha, light aromatic 64742-95-6     | Part 5, Other Groups and Mixtures  |
| 1,2,4-Trimethylbenzene (constituent)<br>95-63-6  | Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999   |
| Ethylene glycol monopropyl ether 2807-30-9       | Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999   |
| 1,3,5-Trimethylbenzene (constituent)<br>108-67-8 | Part 5, Isomer Groups total of 1,2,3-Trimethylbenzene, CAS No. 526-73-8, and 1,3,5-Trimethylbenzene, CAS No. 108-67-8, except 1,2,4-Trimethylbenzene, CAS No. 95-63-6 Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999   |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7        | Part 1, Group A Substance total of all isomers of Xylene, including m-Xylene, CAS No. 108-38-3, o-Xylene, CAS No. 95-47-6, and p-Xylene, CAS No. 106-42-3 Part 5, Isomer Groups total of all isomers of Xylene, including m-Xylene, CAS No. 108-38-3, o-Xylene, CAS No. 95-47-6, and p-Xylene, CAS No. 106-42-3 Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| Cumene (constituent)<br>98-82-8                  | Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999   |
| Ethyl benzene (constituent)                      | Part 1, Group A Substance Part 4 Substance as set out in Section   |

| 100-41-4 | 65 of the List of Toxic Substances in Schedule 1 of the Canadian |
|----------|--|
|          | Environmental Protection Act, 1999                               |

# 16. OTHER INFORMATION

HMIS: Health **Flammability** Reactivity **Personal Protection** 2 \*

# Key or legend to abbreviations and acronyms used in the safety data sheet

#### Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA (time-weighted average) TWA **STEL** STEL (Short Term Exposure Limit)

Maximum limit value Ceiling

#### ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration)

X - Present

**Revision Date** May-30-2015

# **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of MSDS**