

# SAFETY DATA SHEET

Published DateRevision DateRevision NumberJan-23-2024Jan-23-20242.7

# 1. IDENTIFICATION

**Product identifier** 

Product code PX19
Product name Fire Red

Product category PX Series SV Flock Adhesive Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Industrial Printing Operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Barton Road
Heaton Mersey

Tel: +001-913-422-1888 Stockport, England SK4 3EG
Tel: +001-800-677-4657 Tel: +44 161 442 2111

Fax: +001-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: +001-800-424-9300

Outside USA: Chemtrec: +001-703-527-3887

24 Hour Emergency Phone Number

# 2. HAZARDS IDENTIFICATION

#### Classification

Skin sensitization	Category 1 - (H317)
Carcinogenicity	Category 1B - (H350)
Aspiration hazard	Category 1 - (H304)
Flammable liquids	Category 3 - (H226)

### Label elements







# Signal word Danger

#### **Hazard statements**

H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H317 - May cause an allergic skin reaction

H350 - May cause cancer

#### **Precautionary Statements**

P201 - Obtain special instructions before use

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P331 - Do NOT induce vomiting

P403 + P235 - Store in a well-ventilated place. Keep cool

#### Hazards not otherwise classified (HNOC)

No information available.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Inhalation

Chemical name	CAS No.	Weight-%	Trade	Note
		_	secret	
Petroleum distillates, hydrotreated light	64742-47-8	10 - 30	*	
Naphtha, petroleum, hydrotreated heavy	64742-48-9	5 - 10	*	
Ethyl alcohol	64-17-5	1 - 5	*	
2-Butanone, oxime	96-29-7	0.1 - < 1	*	
Cobalt Compounds	Not Available	0.1 - < 1	*	

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST-AID MEASURES

#### Description of first aid measures

**General Advice** Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

**Skin Contact** Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention. Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

# Most important symptoms and effects, both acute and delayed

None under normal use conditions.

# Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

# **Suitable Extinguishing Media**

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### **Unsuitable Extinguishing Media**

No information available.

# **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

#### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

#### **Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

**Handling** Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

# Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open

flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep

out of the reach of children.

**Incompatible Products** Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### **Exposure limits**

Chemical name	ACGIH TLV
Ethyl alcohol	STEL: 1000 ppm
64-17-5	
Chemical name	OSHA PEL
Ethyl alcohol	TWA: 1000 ppm
64-17-5	TWA: 1900 mg/m <sup>3</sup>
Chemical name	OSHA PEL (vacated)
	T144 4000

Chemical name	OSHA PEL (vacated)
Ethyl alcohol	TWA: 1000 ppm
64-17-5	TWA: 1900 mg/m <sup>3</sup>

Chemical name	Ontario TWAEV
Ethyl alcohol	STEL: 1000 ppm
64-17-5	

Chemical name	Mexico OEL (TWA)

Ethyl alcohol	STEL/PPT-CT: 1000 ppm
64-17-5	

#### **Appropriate engineering controls**

**Engineering Measures** Provide a good standard of general ventilation. Natural ventilation is from doors, windows

> etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In

case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

**Skin Protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as

appropriate, to prevent skin contact.

**Hand Protection** Chemical resistant protective gloves.

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6,

corresponding >480 minutes of permeation time): eq. nitrile rubber (0.4 mm), chloroprene

rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a

chemical-protective glove in practice may be much shorter than the permeation time

determined through testing.

Due to different glove types, the manufacturer's directions for use should be observed.

Replace gloves immediately when torn or any change in appearance is noticed such as

dimension, color, flexibility.

**Respiratory Protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of

the material.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

No data available

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Liquid Colored Physical state **Appearance** 

Odor Characteristic **Odor Threshold** No information available

**Property** Values Remarks • Method No data available

**Melting Point / Freezing Point** No information available > 149 °C / 300 °F **Boiling Point / Boiling Range** 

Flash Point 49 °C / 120 °F Pensky Martens Closed Cup (PMCC)

No data available **Evaporation rate** 

Flammability Limit in Air Upper flammability limit No data available

No data available Lower flammability limit **Vapor Pressure** No data available **Vapor Density** No data available

**Specific Gravity** 0.99

No data available

Water Solubility
Solubility in other solvents
Partition coefficient: n-octanol/water
Autoignition Temperature
No information available
Hyphen
No data available

Explosive Properties No data available Oxidizing Properties No data available

Other information

**Dynamic viscosity** 

Photochemically Reactive No Weight Per Gallon (lbs/gal) 8.26

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
39.5	42.92	3.26	391.21

# 10. STABILITY AND REACTIVITY

#### Reactivity

No information available.

#### Chemical stability

Stable under normal conditions.

#### Possibility of hazardous reactions

None under normal processing.

# Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

# Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

#### 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

InhalationSpecific test data for the substance or mixture is not available.Eye ContactSpecific test data for the substance or mixture is not available.Skin ContactSpecific test data for the substance or mixture is not available.IngestionSpecific test data for the substance or mixture is not available.

Chemical name	Oral LD50
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)
Naphtha, petroleum, hydrotreated heavy 64742-48-9	> 6000 mg/kg (Rat)
Ethyl alcohol 64-17-5	= 7060 mg/kg (Rat)
2-Butanone, oxime 96-29-7	= 930 mg/kg (Rat)

Chemical name	Dermal LD50
Petroleum distillates, hydrotreated light >	> 2000 mg/kg (Rabbit)

64742-47-8	
Naphtha, petroleum, hydrotreated heavy	> 5000 mg/kg (Rabbit)
64742-48-9	
2-Butanone, oxime	1000 - 1800 mg/kg (Rabbit)
96-29-7	
Cobalt Compounds	> 5000 mg/kg (Rabbit)

Chemical name	Inhalation LC50
Petroleum distillates, hydrotreated light 64742-47-8	> 5.2 mg/L (Rat)4 h
Naphtha, petroleum, hydrotreated heavy 64742-48-9	> 8500 mg/m³ (Rat ) 4 h
Ethyl alcohol 64-17-5	= 116.9 mg/L (Rat)4 h = 133.8 mg/L (Rat)4 h
2-Butanone, oxime 96-29-7	> 4.83 mg/L (Rat)4 h
Cobalt Compounds	> 10 mg/L (Rat)1 h

# Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Specific test data for the substance or mixture is not available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationSpecific test data for the substance or mixture is not available.Eye damage/irritationSpecific test data for the substance or mixture is not available.IrritationSpecific test data for the substance or mixture is not available.CorrosivitySpecific test data for the substance or mixture is not available.

Sensitization Specific test data for the substance or mixture is not available. May cause an allergic skin

reaction. (based on components).

Mutagenic Effects Specific test data for the substance or mixture is not available.

Carcinogenic effects Specific test data for the substance or mixture is not available. May cause cancer. (based

on components).

Reproductive Effects
Specific test data for the substance or mixture is not available.
STOT - single exposure
STOT - repeated exposure
Chronic Toxicity
Specific test data for the substance or mixture is not available.
Specific test data for the substance or mixture is not available.
Specific test data for the substance or mixture is not available.

Aspiration hazard Specific test data for the substance or mixture is not available. May be fatal if swallowed and

enters airways. (based on components).

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH
Ethyl alcohol	A3
64-17-5	

Chemical name	IARC
Cobalt Compounds	Group 2B

# Numerical measures of toxicity - Product Information

Unknown acute toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 22,727.30 mg/kg

 ATEmix (dermal)
 99,999.00 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 mg/l

 ATEmix (inhalation-dust/mist)
 99,999.00 mg/l

ATEmix (inhalation-vapor) 99,999.00 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Specific test data for the substance or mixture is not available.

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants
2-Butanone, oxime	72h EC50 Desmodesmus subspicatus: = 83 mg/L
96-29-7	

Chemical name	Fish
Petroleum distillates, hydrotreated light	96h LC50 Pimephales promelas: = 45 mg/L (flow-through)
64742-47-8	96h LC50 Lepomis macrochirus: = 2.2 mg/L (static)
	96h LC50 Oncorhynchus mykiss: = 2.4 mg/L (static)
Naphtha, petroleum, hydrotreated heavy	96h LC50 Pimephales promelas: = 2200 mg/L
64742-48-9	
Ethyl alcohol	96h LC50 Pimephales promelas: 13400 - 15100 mg/L
64-17-5	(flow-through)
	96h LC50 Oncorhynchus mykiss: 12.0 - 16.0 mL/L (static)
	96h LC50 Pimephales promelas: > 100 mg/L (static)
2-Butanone, oxime	96h LC50 Pimephales promelas: 777 - 914 mg/L (flow-through)
96-29-7	96h LC50 Poecilia reticulata: = 760 mg/L (static)

Chemical name	Crustacea
Ethyl alcohol	48h LC50 Daphnia magna: 9268 - 14221 mg/L
64-17-5	48h EC50 Daphnia magna: = 2 mg/L Static
2-Butanone, oxime	48h EC50 Daphnia magna: = 750 mg/L
96-29-7	

# **Persistence and Degradability**

No information available.

#### **Bioaccumulation**

Chemical name	Partition coefficient
Ethyl alcohol	-0.32
64-17-5	
2-Butanone, oxime	0.65
96-29-7	

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. TRANSPORT INFORMATION

**Note:** This information is not intended to convey all specific transportation requirements relating to

this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation

information can be found in the specific regulations for your mode of transportation. It is the

responsibility of the transporting organization to follow all applicable laws, regulations and

rules relating to the transportation of the material.

In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not DOT

regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part

1.33]. UN1210

UN/ID no **Proper Shipping Name** Printing Ink

Transport hazard class(es) **Packing Group** Ш

ICAO / IATA / IMDG / IMO

UN/ID no UN1210 **Proper Shipping Name** Printing Ink

Transport hazard class(es) Ш **Packing Group** 

# 15. REGULATORY INFORMATION

#### International Inventories

All substances are listed as ACTIVE on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

# **U.S. Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Manganese Compounds	Not Available	1 - 5	1.0

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air

Chemical name	CAS No.	Weight-%
Manganese Compounds	Not Available	1 - 5
Manganese Compounds	Not Available	0.1 - < 1
Cobalt Compounds	Not Available	0.1 - < 1

# **US State Regulations**

Chemical name	Massachusetts
Ethyl alcohol	X
64-17-5	

	Minnesota Right To Know
Ethyl alcohol 64-17-5	X
2-Butanone, oxime 96-29-7	X

Chemical name	New Jersey
Ethyl alcohol	X
64-17-5	
Cobalt Compounds	X

Chemical name	Pennsylvania
Ethyl alcohol	X
64-17-5	
Cobalt Compounds	X

# **California Proposition 65**

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

#### Canada

Chemical name	NPRI - National Pollutant Release Inventory
Petroleum distillates, hydrotreated light	Part 5 Substance - Volatile Organic Compounds with Additional
64742-47-8	Reporting Requirements
Naphtha, petroleum, hydrotreated heavy	Part 5 Substance - Volatile Organic Compounds with Additional
64742-48-9	Reporting Requirements
Ethyl alcohol	Part 5 Substance - Volatile Organic Compounds with Additional
64-17-5	Reporting Requirements
	Part 4 Substance - Criteria Air Contaminants
Cobalt Compounds	Part 1, Group B Substance
·	·

#### 16. OTHER INFORMATION

# Key or legend to abbreviations and acronyms used in the safety data sheet

#### Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA (time-weighted average) TWA STEL STEL (Short Term Exposure Limit)

Maximum limit value Ceiling

#### ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

#### IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen

**OSHA: (Occupational Safety & Health Administration)** 

X - Present

**Revision Date** Jan-23-2024

#### Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

# Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**