



Print Date May-31-2015 Revision Date May-30-2015 Revision Number

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

| Product identifier | |
|--------------------|--|
| Product code | 8411 |
| Product name | Lemon Yellow |
| Product category | 8400 Series CVIM Conventional Insert Mold Decorating Screen Ink |

Other means of identification Synonyms None

 Recommended use of the chemical and restrictions on use

 Recommended use
 Printing operations

Details of the supplier of the safety data sheet

UNITED STATES Nazdar Company 8501 Hedge Lane Terrace Shawnee, KS 66227 Tel: 1-913-422-1888 Tel: 1-800-677-4657 Fax: 1-913-422-2294 www.nazdar.com UNITED KINGDOM Nazdar Limited Barton Road Heaton Mersey Stockport, England SK4 3EG Tel: +44 161 442 2111

Emergency telephone number

USA: Chemtrec: 1-800-424-9300 Outside USA: Chemtrec: 1-703-527-3887 24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

| Aspiration toxicity | Category 1 - (H304) |
|--------------------------|---------------------|
| Chronic aquatic toxicity | Category 3 - (H412) |
| Flammable liquids | Category 3 - (H226) |

Label elements



Signal Word Danger

Hazard Statements

H304 - May be fatal if swallowed and enters airways H412 - Harmful to aquatic life with long lasting effects H226 - Flammable liquid and vapor

Precautionary Statements

P331 - Do NOT induce vomiting

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P273 - Avoid release to the environment

Hazards not otherwise classified (HNOC)

May be harmful if swallowed. May be harmful in contact with skin. Harmful to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

| Component | CAS-No | Weight % | Trade Secret | Note |
|--------------------------------------|--------------|----------|-----------------|------|
| Naphtha (petroleum), heavy aromatic | 64742-94-5 | 10 - 30 | * | |
| Cyclohexanone | 108-94-1 | 10 - 30 | * | |
| Vanadium Compounds | Trade Secret | 5 - 10 | * | |
| Gamma Butyrolactone | 96-48-0 | 5 - 10 | * | |
| Dimethyl Glutarate | 1119-40-0 | 1 - 5 | * | |
| Naphthalene (constituent) | 91-20-3 | 1 - 5 | * | 1 |
| Kaolin | 1332-58-7 | 1 - 5 | * | |
| Titanium dioxide | 13463-67-7 | 1 - 5 | * | |
| Dimethyl Succinate | 106-65-0 | 1 - 5 | * | |
| Dimethyl Adipate | 627-93-0 | 1 - 5 | * | |
| 1,2,4-Trimethylbenzene (constituent) | 95-63-6 | < 1 | * | 1 |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

4. FIRST AID MEASURES

Description of first aid measures

| General Advice Eye Contact | Show this safety data sheet to the doctor in attendance. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists. |
|-------------------------------|---|
| Skin Contact | Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention. |
| Inhalation | Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately. |
| Ingestion | DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. |

Most important symptoms and effects, both acute and delayed None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

| Handling | Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. | | |
|--|--|--|--|
| Conditions for safe storage, including any incompatibilities | | | |
| Storage | Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children. | | |
| Incompatible Products | Strong acids. Strong bases. Strong oxidizing agents. Reducing agent. | | |
| 8. EXPOSURE CONTROLS/PERSONAL PROTECTION | | | |

Control parameters

Exposure limits

| Component | ACGIH TLV | |
|---------------------------|--|--|
| Cyclohexanone | TWA: 20 ppm | |
| 108-94-1 | STEL: 50 ppm | |
| | Skin | |
| Naphthalene (constituent) | TWA: 10 ppm | |
| 91-20-3 | STEL: 15 ppm | |
| | Skin | |
| Kaolin | TWA: 2 mg/m ³ (respirable fraction) | |
| 1332-58-7 | | |
| Titanium dioxide | TWA: 10 mg/m ³ | |
| 13463-67-7 | | |
| Component | OSHA PEL | |
| Cyclohexanone | TWA: 25 ppm | |
| 108-94-1 | TWA: 100 mg/m ³ | |
| | TWA: 50 ppm | |

| | TWA: 200 mg/m³ Skin |
|--------------------------------------|--|
| Naphthalene (constituent) 91-20-3 | TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³ |
| Kaolin 1332-58-7 | TWA: 10 mg/m ³ (total dust) TWA: 5 mg/m ³ (respirable fraction) TWA: 15 mg/m ³ (total dust) |
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ (total dust) TWA: 15 mg/m ³ (total dust) |

| Component | Ontario TWAEV |
|--------------------------------------|--|
| Cyclohexanone 108-94-1 | TWA: 20 ppm STEL: 50 ppm |
| | Skin |
| Naphthalene (constituent) 91-20-3 | TWA: 10 ppm STEL: 15 ppm Skin |
| Kaolin 1332-58-7 | TWA: 2 mg/m³ (respirable) |
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ (total dust) |

| Component | Mexico OEL (TWA) |
|--|--|
| Cyclohexanone | TWA/LMPE-PPT: 50 ppm |
| 108-94-1 | TWA/LMPE-PPT: 200 mg/m ³ |
| | STEL/LMPE-CT: 100 ppm |
| | STEL/LMPE-CT: 400 mg/m ³ |
| Naphthalene (constituent) TWA/LMPE-PPT: 10 ppm | |
| 91-20-3 | TWA/LMPE-PPT: 50 mg/m ³ |
| | STEL/LMPE-CT: 15 ppm |
| | STEL/LMPE-CT: 75 mg/m ³ |
| Kaolin | TWA/LMPE-PPT: 10 mg/m ³ |
| 1332-58-7 | STEL/LMPE-CT: 20 mg/m ³ |
| Titanium dioxide | TWA/LMPE-PPT: 10 mg/m ³ (as Ti) |
| 13463-67-7 | STEL/LMPE-CT: 20 mg/m ³ (as Ti) |

Appropriate engineering controls

| Engineering Measures | Provide a good standard of general ventilation. Natural ventilation is from doors, windows |
|----------------------|---|
| | etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In |
| | case of insufficient ventilation, wear suitable respiratory equipment. |

Individual protection measures, such as personal protective equipment

| Eye/face Protection | Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location. |
|--------------------------------|--|
| Skin Protection | Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. |
| Respiratory Protection | If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. |
| General Hygiene Considerations | Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Information on basic physical a Physical State Odor | <u>and chemical properties</u> Liquid Characteristic | Appearance Odor Threshold | Colored Liquid No information available |
|---|--|--|--|
| Property pH Melting point/freezing point Boiling point/Boiling Range Flash Point Evaporation rate | <u>Values</u> > 149 °C / 300 °F 44 °C / 111 °F | Remarks • Method No data available No data available Tag closed cup No data available | |
| Flammability Limit in Air Upper flammability limit Lower flammability limit Vapor Pressure Vapor Density Specific Gravity Water Solubility Solubility in other solvents Partition coefficient: n-octanol Autoignition Temperature Decomposition temperature Kinematic viscosity Dynamic viscosity | 1.15 /water | No data available No data available | |
| Explosive Properties Oxidizing Properties | No data available No data available | | |
| Other Information Photochemically Reactive | Yes | | |
| Weight Per Gallon (lbs/gal) | 9.59 | | |
| VOC by weight % (less water) 56.7 | VOC by volume % (less water) 56.71 | VOC lbs/gal (less water) 5.44 | VOC grams/liter (less water) 651.98 |

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| Inhalation | There is no data for this product. |
|-------------|------------------------------------|
| Eye Contact | There is no data for this product. |

| Skin Contact Ingestion | There is no data for this product. There is no data for this product. | |
|-------------------------------------|--|-------------------|
| Component | | Oral LD50 |
| Naphtha (petroleum), heavy aromatic | ; | >5000 mg/kg (Rat) |
| | | |

| 64742-94-5 | |
|---|--------------------|
| Cyclohexanone 108-94-1 | 800 mg/kg (Rat) |
| Gamma Butyrolactone 96-48-0 | 1540 mg/kg (Rat) |
| Dimethyl Glutarate 1119-40-0 | 8191 mg/kg (Rat) |
| Naphthalene (constituent) 91-20-3 | 490 mg/kg (Rat) |
| Titanium dioxide 13463-67-7 | >10000 mg/kg (Rat) |
| Dimethyl Succinate 106-65-0 | >5000 mg/kg (Rat) |
| Dimethyl Adipate 627-93-0 | 1920 mg/kg (Rat) |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | 3400 mg/kg (Rat) |

| Component | LD50 Dermal |
|---|--|
| Naphtha (petroleum), heavy aromatic 64742-94-5 | >2000 mg/kg (Rabbit) |
| Naphthalene (constituent) 91-20-3 | >2500 mg/kg (Rat) >20 g/kg (Rabbit) |
| Dimethyl Succinate 106-65-0 | >5000 mg/kg (Rabbit) |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | >3160 mg/kg (Rabbit) |

| Component | Inhalation LC50 |
|---|---|
| Naphtha (petroleum), heavy aromatic 64742-94-5 | >590 mg/m³(Rat)4 h |
| Cyclohexanone 108-94-1 | 8000 ppm (Rat)4 h 10.7 mg/L (Rat)4 h |
| Gamma Butyrolactone 96-48-0 | >2.68 mg/L (Rat)4 h |
| Dimethyl Glutarate 1119-40-0 | >5.6 mg/L (Rat)4 h |
| Naphthalene (constituent) 91-20-3 | >340 mg/m³(Rat)1 h |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | 18 g/m³(Rat)4 h |

Information on toxicological effects

Symptoms

There is no data for this product.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| Skin corrosion/irritation | There is no data for this product. | |
|---------------------------|------------------------------------|---|
| Eye damage/irritation | There is no data for this product. | |
| Irritation | There is no data for this product. | |
| Corrosivity | There is no data for this product. | |
| Sensitisation | There is no data for this product. | |
| Mutagenic Effects | There is no data for this product. | |
| Reproductive Effects | There is no data for this product. | |
| STOT - single exposure | There is no data for this product. | |
| STOT - repeated exposure | There is no data for this product. | |
| Chronic Toxicity | There is no data for this product | |
| Aspiration hazard | There is no data for this product. | |
| Carcinogenicity | The table below indicates whether | er each agency has listed any ingredient as a carcinogen. |
| Component | | ACGIH |

| Cyclohexanone 108-94-1 | A3 |
|--------------------------------------|------------------------|
| | |
| Component | IARC |
| Naphthalene (constituent) 91-20-3 | Group 2B |
| Titanium dioxide 13463-67-7 | Group 2B |
| Component | NTP |
| Naphthalene (constituent) 91-20-3 | Reasonably Anticipated |
| Component | OSHA |
| Naphthalene (constituent) 91-20-3 | X |
| Titanium dioxide 13463-67-7 | X |

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

| ATEmix (oral) | 3,123.00 mg/kg |
|-------------------------------|----------------|
| ATEmix (dermal) | 4,996.00 mg/kg |
| ATEmix (inhalation-dust/mist) | 9.00 mg/l |
| ATEmix (inhalation-vapor) | 66.00 mg/l |

12. ECOLOGICAL INFORMATION

Ecotoxicity

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Component | Algae/aquatic plants |
|---|--|
| Cyclohexanone 108-94-1 | 96h EC50 Chlorella vulgaris: 20 mg/L |
| Gamma Butyrolactone 96-48-0 | 72h EC50 Desmodesmus subspicatus: 360 mg/L 96h EC50 Desmodesmus subspicatus: 79 mg/L |
| Naphthalene (constituent) 91-20-3 | 72h EC50 Skeletonema costatum: 0.4 mg/L |
| Component | Fish |
| Cyclohexanone 108-94-1 | 96h LC50 Pimephales promelas: 481 - 578 mg/L [flow-through] |
| Gamma Butyrolactone 96-48-0 | 96h LC50 Leuciscus idus: 220 - 460 mg/L [static] |
| Dimethyl Glutarate 1119-40-0 | 96h LC50 Pimephales promelas: 19.6 - 26.2 mg/L [static] |
| Naphthalene (constituent) 91-20-3 | 96h LC50 Oncorhynchus mykiss: 0.91 - 2.82 mg/L [static] 96h LC50 Pimephales promelas: 5.74 - 6.44 mg/L [flow-through] 96h LC50 Oncorhynchus mykiss: 1.6 mg/L [flow-through] 96h LC50 Pimephales promelas: 1.99 mg/L [static] 96h LC50 Lepomis macrochirus: 31.0265 mg/L [static] |
| Dimethyl Succinate 106-65-0 | 96h LC50 Brachydanio rerio: 50 - 100 mg/L [static] |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | 96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through] |

| Component | Crustacea |
|--------------------------------|--|
| Cyclohexanone 108-94-1 | 24h EC50 Daphnia magna: 800 mg/L |
| Gamma Butyrolactone 96-48-0 | 48h EC50 Daphnia magna Straus: >500 mg/L |

| Dimethyl Glutarate 1119-40-0 | 48h EC50 Daphnia magna: 122.1 - 163.5 mg/L |
|---|---|
| Naphthalene (constituent) 91-20-3 | 48h EC50 Daphnia magna: 1.09 - 3.4 mg/L [static] 48h EC50 Daphnia magna: 1.96 mg/L [Flow through] 48h LC50 Daphnia magna: 2.16 mg/L |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | 48h EC50 Daphnia magna: 6.14 mg/L |

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

| Component | Partition coefficient |
|---|-----------------------|
| Naphtha (petroleum), heavy aromatic | 4.5 |
| 64742-94-5 | |
| Cyclohexanone 108-94-1 | 0.86 |
| Gamma Butyrolactone 96-48-0 | -0.566 |
| Naphthalene (constituent) 91-20-3 | 3.3 |
| Dimethyl Succinate 106-65-0 | 0.19 |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | 3.63 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

| Waste treatment methods | |
|-------------------------|--|
| Waste Disposal Methods | Contain and dispose of waste according to local regulations. |
| Contaminated Packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. |

14. TRANSPORT INFORMATION

| DOT | In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33]. |
|--------------------------|--|
| UN/ID no. | UN1210 |
| Proper Shipping Name | Printing Ink |
| Hazard Class | 3 |
| Packing Group | III |
| ICAO / IATA / IMDG / IMO | |
| UN/ID no. | UN1210 |
| Proper Shipping Name | Printing Ink |
| Hazard Class | 3 |
| Packing Group | |

15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical
or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.ComponentCAS-NoWeight %SARA 313 - Threshold
Values

| •••••••••••• | 0110110 | | Values |
|---------------------------|--------------|--------|--------|
| Vanadium Compounds | Trade Secret | 5 - 10 | 1.0 |
| Naphthalene (constituent) | 91-20-3 | 1 - 5 | 0.1 |

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

| Component | CAS-No | Weight % |
|---------------------------|---------|----------|
| Naphthalene (constituent) | 91-20-3 | 1 - 5 |

U.S. State Regulations

| Component | Massachusetts Right To Know | | |
|---|--------------------------------|--|--|
| Cyclohexanone 108-94-1 | X | | |
| Naphthalene (constituent) 91-20-3 | X | | |
| Kaolin 1332-58-7 | X | | |
| Titanium dioxide 13463-67-7 | X | | |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | X | | |

| Component | Minnesota Right To Know |
|---|----------------------------|
| Cyclohexanone 108-94-1 | X |
| Naphthalene (constituent) 91-20-3 | X |
| Kaolin 1332-58-7 | X |
| Titanium dioxide 13463-67-7 | X |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | X |

| Component | New Jersey Right To Know | | |
|---|-----------------------------|--|--|
| Cyclohexanone 108-94-1 | × | | |
| Vanadium Compounds | X | | |
| Naphthalene (constituent) 91-20-3 | X | | |
| Kaolin 1332-58-7 | X | | |
| Titanium dioxide 13463-67-7 | X | | |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | X | | |

| Component | Pennsylvania Right To Know |
|--------------------------------------|-------------------------------|
| Cyclohexanone 108-94-1 | Х |
| Naphthalene (constituent) 91-20-3 | Х |

| Kaolin 1332-58-7 | X |
|---|---|
| Titanium dioxide 13463-67-7 | Х |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | Х |

California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

| Component | California Prop. 65 | |
|---------------------------|---------------------|--|
| Naphthalene (constituent) | Carcinogen | |
| Titanium dioxide | Carcinogen | |

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

<u>Canada</u>

| Component | NPRI - National Pollutant Release Inventory |
|---|---|
| Naphtha (petroleum), heavy aromatic 64742-94-5 | Part 5, Other Groups and Mixtures Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| Cyclohexanone 108-94-1 | Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| Vanadium Compounds | Part 1, Group A Substance total of pure Vanadium and the equivalent weight of Vanadium contained in any compound or mixture, except Vanadium contained in an alloy |
| Gamma Butyrolactone 96-48-0 | Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| Dimethyl Glutarate 1119-40-0 | Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| Naphthalene (constituent) 91-20-3 | Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| Dimethyl Succinate 106-65-0 | Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| Dimethyl Adipate 627-93-0 | Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |

| 16. OTHER INFORMATION | | | | |
|-----------------------|--------------------------|--------------------------|------------------------|--------------------------|
| HMIS: | Health 3 * | Flammability 2 | Reactivity 0 | Personal Protection X |
| Key or legend to : | abbreviations and acrony | uns used in the safety d | ata shoot | |

Key or legend to abbreviations and acronyms used in the safety data sheet

| Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION | |
|---|----------------------------------|
| TWA | TWA (time-weighted average) |
| STEL | STEL (Short Term Exposure Limit) |
| Ceiling | Maximum limit value |

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen
IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans **NTP: (National Toxicity Program)** Known - Known Carcinogen Reasonably Anticipated to be a Human Carcinogen **OSHA: (Occupational Safety & Health Administration)** X - Present

Revision Date May-30-2015

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of MSDS