

# SAFETY DATA SHEET

Print DateRevision DateRevision NumberJun-01-2015May-31-20151

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product code VF114
Product name Brown

Product category VF Series Flat Vinyl Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Burton Road
Heaton Mersey

Tel: 1-913-422-1888 Stockport, England SK4 3EG
Tel: 1-800-677-4657 Tel: +44 161 442 2111

Fax: 1-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: 1-800-424-9300

Outside USA: Chemtrec: 1-703-527-3887 24 Hour Emergency Phone Number

# 2. HAZARDS IDENTIFICATION

#### Classification

Serious eye damage/eye irritation	Category 2 - (H319)
Aspiration toxicity	Category 1 - (H304)
Flammable liquids	Category 3 - (H226)

#### Label elements







#### Signal Word Danger

#### **Hazard Statements**

H304 - May be fatal if swallowed and enters airways

H319 - Causes serious eye irritation H226 - Flammable liquid and vapor

#### **Precautionary Statements**

Revision Date May-31-2015

VF114 - Brown

P331 - Do NOT induce vomiting

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

#### Hazards not otherwise classified (HNOC)

May be harmful if swallowed. May be harmful in contact with skin.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### **Mixture**

Component	CAS-No	Weight %	Trade Secret	Note
Naphtha (petroleum), heavy aromatic	64742-94-5	30 - 60	*	
Talc	14807-96-6	10 - 30	*	
Iron oxide	1309-37-1	5 - 10	*	
Gamma Butyrolactone	96-48-0	5 - 10	*	
Diacetone alcohol	123-42-2	5 - 10	*	
Cyclohexanone	108-94-1	5 - 10	*	
Naphthalene (constituent)	91-20-3	1 - 5	*	1
1,2,4-Trimethylbenzene (constituent)	95-63-6	< 0.5	*	1
Quartz, crystalline silica	14808-60-7	< 0.5	*	
Crystalline silica (cristobalite)	14464-46-1	< 0.5	*	

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

#### 4. FIRST AID MEASURES

#### **Description of first aid measures**

**General Advice** Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

**Inhalation** Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

Ingestion DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

# Most important symptoms and effects, both acute and delayed

None under normal use conditions.

#### Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

#### **Suitable Extinguishing Media**

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### **Unsuitable Extinguishing Media**

No information available.

#### **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Revision Date May-31-2015

VF114 - Brown

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

# 6. ACCIDENTAL RELEASE MEASURES

# Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

#### **Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

#### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Handling Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

#### Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from Storage

open flames, hot surfaces and sources of ignition. Keep container closed when not in use.

Keep out of the reach of children.

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent. **Incompatible Products** 

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

# **Exposure limits**

Component	ACGIH TLV	
Talc 14807-96-6	TWA: 2 mg/m³ (particulate matter)	
Iron oxide 1309-37-1	TWA: 5 mg/m³ (respirable fraction)	
Diacetone alcohol 123-42-2	TWA: 50 ppm	
Cyclohexanone 108-94-1	TWA: 20 ppm STEL: 50 ppm Skin	
Naphthalene (constituent) 91-20-3	TWA: 10 ppm STEL: 15 ppm Skin	
Quartz, crystalline silica 14808-60-7	TWA: 0.025 mg/m³ (respirable fraction)	
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.025 mg/m³ (respirable fraction)	

Component	OSHA PEL
Talc	TWA: 2 mg/m³ (respirable dust)
14807-96-6	

Iron oxide 1309-37-1	TWA: 10 mg/m³ (fume)	
Diacetone alcohol 123-42-2	TWA: 50 ppm TWA: 240 mg/m³	
Cyclohexanone 108-94-1	TWA: 25 ppm TWA: 100 mg/m³ TWA: 50 ppm TWA: 200 mg/m³ Skin	
Naphthalene (constituent) 91-20-3	TWA: 10 ppm TWA: 50 mg/m³ STEL: 15 ppm STEL: 75 mg/m³	
Quartz, crystalline silica 14808-60-7	TWA: 0.1 mg/m³ (respirable dust)	
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.05 mg/m³ (respirable dust)	

Component	Ontario TWAEV		
Talc 14807-96-6	TWA: 2 mg/m³ (respirable)		
Iron oxide 1309-37-1	TWA: 5 mg/m³ (respirable)		
Diacetone alcohol 123-42-2	TWA: 50 ppm TWA: 240 mg/m³ STEL: 75 ppm STEL: 360 mg/m³		
Cyclohexanone 108-94-1	TWA: 20 ppm STEL: 50 ppm Skin		
Naphthalene (constituent) 91-20-3	TWA: 10 ppm STEL: 15 ppm Skin		
Quartz, crystalline silica 14808-60-7	TWA: 0.10 mg/m³ (respirable)		
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.05 mg/m³ (respirable)		

Component	Mexico OEL (TWA)
Talc 14807-96-6	TWA/LMPE-PPT: 2 mg/m³ (respirable fraction)
Iron oxide 1309-37-1	TWA/LMPE-PPT: 5 mg/m³ STEL/LMPE-CT: 10 mg/m³ (as Fe)
Diacetone alcohol 123-42-2	TWA/LMPE-PPT: 50 ppm TWA/LMPE-PPT: 240 mg/m³ STEL/LMPE-CT: 75 ppm STEL/LMPE-CT: 360 mg/m³
Cyclohexanone 108-94-1	TWA/LMPE-PPT: 50 ppm TWA/LMPE-PPT: 200 mg/m³ STEL/LMPE-CT: 100 ppm STEL/LMPE-CT: 400 mg/m³
Naphthalene (constituent) 91-20-3	TWA/LMPE-PPT: 10 ppm TWA/LMPE-PPT: 50 mg/m³ STEL/LMPE-CT: 15 ppm STEL/LMPE-CT: 75 mg/m³
Quartz, crystalline silica 14808-60-7	TWA/LMPE-PPT: 0.1 mg/m³ (respirable fraction)
Crystalline silica (cristobalite) 14464-46-1	TWA/LMPE-PPT: 0.05 mg/m³ (respirable fraction)

# **Appropriate engineering controls**

# **Engineering Measures**

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

**Eye/face Protection** Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

**Skin Protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in

accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid Appearance Colored Liquid

Odor Characteristic Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No data available
Melting point/freezing point No data available

Boiling point/Boiling Range > 149 °C / 300 °F

Flash Point 52 °C / 125 °F Setaflash closed cup

Evaporation rate No data available

Flammability Limit in Air

Upper flammability limit
Lower flammability limit
No data available
Vapor Pressure
No data available
Vapor Density
No data available
No data available

Specific Gravity 1.26

Water Solubility

No data available
Solubility in other solvents

No data available
Partition coefficient: n-octanol/water

Autoignition Temperature

No data available
Decomposition temperature

No data available

Explosive Properties No data available
Oxidizing Properties No data available

**Other Information** 

Photochemically Reactive Yes Weight Per Gallon (lbs/gal) 10.47

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
53.21	65.84	5.58	

# 10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

# Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

# **Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

InhalationThere is no data for this product.Eye ContactThere is no data for this product.Skin ContactThere is no data for this product.IngestionThere is no data for this product.

Component	Oral LD50	
Naphtha (petroleum), heavy aromatic 64742-94-5	>5000 mg/kg(Rat)	
lron oxide 1309-37-1	>10000 mg/kg(Rat)	
Gamma Butyrolactone 96-48-0	1540 mg/kg(Rat)	
Diacetone alcohol 123-42-2	4 g/kg (Rat)	
Cyclohexanone 108-94-1	800 mg/kg ( Rat )	
Naphthalene (constituent) 91-20-3	490 mg/kg ( Rat )	
1,2,4-Trimethylbenzene (constituent) 95-63-6	3400 mg/kg(Rat)	
Quartz, crystalline silica 14808-60-7	500 mg/kg (Rat)	

Component	LD50 Dermal
Naphtha (petroleum), heavy aromatic 64742-94-5	>2000 mg/kg(Rabbit)
Diacetone alcohol 123-42-2	13500 mg/kg(Rabbit)
Naphthalene (constituent) 91-20-3	>2500 mg/kg(Rat) >20 g/kg(Rabbit)
1,2,4-Trimethylbenzene (constituent) 95-63-6	>3160 mg/kg(Rabbit)

Component	Inhalation LC50
Naphtha (petroleum), heavy aromatic 64742-94-5	>590 mg/m³ (Rat) 4 h
Gamma Butyrolactone 96-48-0	>2.68 mg/L (Rat) 4 h
Cyclohexanone 108-94-1	8000 ppm (Rat)4 h 10.7 mg/L (Rat)4 h
Naphthalene (constituent) 91-20-3	>340 mg/m³ (Rat) 1 h
1,2,4-Trimethylbenzene (constituent) 95-63-6	18 g/m³(Rat)4 h

# Information on toxicological effects

Revision Date May-31-2015

VF114 - Brown

**Symptoms** There is no data for this product.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation There is no data for this product. There is no data for this product. Eye damage/irritation Irritation There is no data for this product. Corrosivity There is no data for this product. Sensitisation There is no data for this product. **Mutagenic Effects** There is no data for this product. There is no data for this product. **Reproductive Effects** There is no data for this product. STOT - single exposure There is no data for this product. STOT - repeated exposure **Chronic Toxicity** There is no data for this product **Aspiration hazard** There is no data for this product.

<u>Carcinogenicity</u> The table below indicates whether each agency has listed any ingredient as a carcinogen.

Caroline germenty	ior odori agorioj rido notod dirij irigi odrorit do d odroritogorii
Component	ACGIH
Cyclohexanone 108-94-1	A3

Component	IARC
Naphthalene (constituent)	Group 2B
91-20-3	
Quartz, crystalline silica	Group 1
14808-60-7	
Crystalline silica (cristobalite)	Group 1
14464-46-1	·

Component	NTP
Naphthalene (constituent) 91-20-3	Reasonably Anticipated
Quartz, crystalline silica 14808-60-7	Known

Component	OSHA
Naphthalene (constituent)	X
91-20-3	
Quartz, crystalline silica	X
14808-60-7	
Crystalline silica (cristobalite)	X
14464-46-1	

# Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 4,535.00 mg/kg
ATEmix (dermal) 5,122.00 mg/kg
ATEmix (inhalation-dust/mist) 21.80 mg/l
ATEmix (inhalation-vapor) 160.00 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Gamma Butyrolactone	72h EC50 Desmodesmus subspicatus: 360 mg/L
96-48-0	96h EC50 Desmodesmus subspicatus: 79 mg/L
Cyclohexanone	96h EC50 Chlorella vulgaris: 20 mg/L
108-94-1	

96h LC50 Pimephales promelas: 1.99 mg/L [static] 96h LC50 Lepomis macrochirus: 31.0265 mg/L [static]

96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through]

Naphthalene (constituent) 91-20-3	72h EC50 Skeletonema costatum: 0.4 mg/L
Component	Fish
Talc 14807-96-6	96h LC50 Brachydanio rerio: >100 g/L [semi-static]
Gamma Butyrolactone 96-48-0	96h LC50 Leuciscus idus: 220 - 460 mg/L [static]
Diacetone alcohol 123-42-2	96h LC50 Lepomis macrochirus: 420 mg/L 96h LC50 Lepomis macrochirus: 420 mg/L [static]
Cyclohexanone 108-94-1	96h LC50 Pimephales promelas: 481 - 578 mg/L [flow-through]
Naphthalene (constituent) 91-20-3	96h LC50 Oncorhynchus mykiss: 0.91 - 2.82 mg/L [static] 96h LC50 Pimephales promelas: 5.74 - 6.44 mg/L [flow-through]

Component	Crustacea
Gamma Butyrolactone 96-48-0	48h EC50 Daphnia magna Straus: >500 mg/L
Diacetone alcohol 123-42-2	24h EC50 Daphnia magna: 8750 mg/L
Cyclohexanone 108-94-1	24h EC50 Daphnia magna: 800 mg/L
Naphthalene (constituent) 91-20-3	48h EC50 Daphnia magna: 1.09 - 3.4 mg/L [static] 48h EC50 Daphnia magna: 1.96 mg/L [Flow through] 48h LC50 Daphnia magna: 2.16 mg/L
1,2,4-Trimethylbenzene (constituent) 95-63-6	48h EC50 Daphnia magna: 6.14 mg/L

# Persistence and Degradability

1,2,4-Trimethylbenzene (constituent)

95-63-6

No information available.

# **Bioaccumulation**

No information available.

Component	Partition coefficient
Naphtha (petroleum), heavy aromatic 64742-94-5	4.5
Gamma Butyrolactone 96-48-0	-0.566
Diacetone alcohol 123-42-2	1.03
Cyclohexanone 108-94-1	0.86
Naphthalene (constituent) 91-20-3	3.3
1,2,4-Trimethylbenzene (constituent) 95-63-6	3.63

# Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Contain and dispose of waste according to local regulations. **Waste Disposal Methods** 

Empty containers should be taken to an approved waste handling site for recycling or **Contaminated Packaging** 

disposal.

# 14. TRANSPORT INFORMATION

**DOT** In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not

regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language

Part 1.33].

UN/ID no. UN1210 Proper Shipping Name Printing Ink

Hazard Class 3
Packing Group

ICAO / IATA / IMDG / IMO

UN1210
Proper Shipping Name
UN1210
Printing Ink

Hazard Class 3
Packing Group III

# 15. REGULATORY INFORMATION

#### **International Inventories**

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

#### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Naphthalene (constituent)	91-20-3	1 - 5	0.1

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Component	CAS-No	Weight %
Naphthalene (constituent)	91-20-3	1 - 5

# **U.S. State Regulations**

Component	Massachusetts Right To Know
Talc 14807-96-6	X
Iron oxide 1309-37-1	X
Diacetone alcohol 123-42-2	X
Cyclohexanone 108-94-1	X
Naphthalene (constituent) 91-20-3	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Quartz, crystalline silica 14808-60-7	X
Crystalline silica (cristobalite) 14464-46-1	X

Component	Minnesota Right To Know
Talc 14807-96-6	X

Iron oxide 1309-37-1	X
Diacetone alcohol 123-42-2	X
Cyclohexanone 108-94-1	X
Naphthalene (constituent) 91-20-3	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Quartz, crystalline silica 14808-60-7	X
Crystalline silica (cristobalite) 14464-46-1	X

Component	New Jersey Right To Know
Talc 14807-96-6	X
Iron oxide 1309-37-1	Х
Diacetone alcohol 123-42-2	Х
Cyclohexanone 108-94-1	Х
Naphthalene (constituent) 91-20-3	Х
1,2,4-Trimethylbenzene (constituent) 95-63-6	Х
Quartz, crystalline silica 14808-60-7	X
Crystalline silica (cristobalite) 14464-46-1	X

Component	Pennsylvania Right To Know
Talc 14807-96-6	X
Iron oxide 1309-37-1	X
Diacetone alcohol 123-42-2	X
Cyclohexanone 108-94-1	X
Naphthalene (constituent) 91-20-3	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Quartz, crystalline silica 14808-60-7	X
Crystalline silica (cristobalite) 14464-46-1	X

<u>California Prop. 65</u>
This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Topiodadaro nam		
	Component	California Prop. 65
	Naphthalene (constituent)	Carcinogen
	Quartz, crystalline silica	Carcinogen

This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product

# Canada

Component	NPRI - National Pollutant Release Inventory
Naphtha (petroleum), heavy aromatic	Part 5, Other Groups and Mixtures Part 4 Substance as set out in
64742-94-5	Section 65 of the List of Toxic Substances in Schedule 1 of the

	Canadian Environmental Protection Act, 1999
Gamma Butyrolactone 96-48-0	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Diacetone alcohol 123-42-2	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Cyclohexanone 108-94-1	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Naphthalene (constituent) 91-20-3	Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999

#### **16. OTHER INFORMATION**

HMIS:HealthFlammabilityReactivityPersonal Protection3 \*20X

# Key or legend to abbreviations and acronyms used in the safety data sheet

#### Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

#### ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date May-31-2015

# Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of MSDS**