SAFETY DATA SHEET

Date of issue/Date of revision15 December 2016Version 4.01

Section 1. Identification		
Product name	: Russet	
Product code	: 287196SP	
Other means of identification	: Not available.	
Product type	: Powder.	
Relevant identified uses of Product use	the substance or mixture and uses advised against : Industrial applications.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Manufacturer	: Matthews Paint Company 760 Pittsburgh Drive Delaware, OH 43015	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)	
Technical Phone Number	: 1-800-323-6593	

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: COMBUSTIBLE DUSTS SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 56.8%
GHS label elements	
Hazard pictograms	:
Signal word	: Warning
Hazard statements	: May form combustible dust concentrations in air. May cause respiratory irritation.

Section 2. Hazards identification

Precautionary statements

: Use only outdoors or in a well-ventilated area. Avoid breathing dust.
: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
: Store locked up.
 Dispose of contents and container in accordance with all local, regional, national and international regulations.
: Keep container tightly closed. Keep away from heat, sparks, open flames and hot surfaces No smoking. Sanding and grinding dusts may be harmful if inhaled. Prevent dust accumulation. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.
: Fine dust clouds may form explosive mixtures with air. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat. Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Product name	1	Russet

%	CAS number
≥20 - ≤50 ≥20 - ≤50 ≥10 - ≤20	12001-26-2 1309-37-1 64741-65-7
	≥20 - ≤50 ≥20 - ≤50

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Section 4. First aid measures

Most important symptoms/	effects, acute and delayed
Potential acute health effe	<u>cts</u>
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: May cause respiratory irritation.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/sym</u>	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: Fine dust clouds may form explosive mixtures with air. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides

Product name Russet

Section 5. Fire-fighting measures

Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust

United States	Page: 4/12
---------------	------------

Product name Russet

Section 7. Handling and storage

	coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: Wapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store above the following temperature: 35°C (95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Mica-group minerals	ACGIH TLV (United States, 3/2015).
	TWA: 3 mg/m ³ 8 hours. Form: Respirable
	fraction
	OSHA PEL Z3 (United States, 2/2013).
	TWA: 20 mppcf 8 hours.
diiron trioxide	ACGIH TLV (United States, 3/2015).
	TWA: 5 mg/m ³ 8 hours. Form: Respirable
	fraction
	OSHA PEL (United States, 2/2013).
	TWA: 10 mg/m ³ 8 hours.
Naphtha (petroleum), heavy alkylate	None.
Key to abbreviatio	ns
A = Acceptable Maximum Peak	S = Potential skin absorption
ACGIH = American Conference of Governmental Industrial Hygienists.	SR = Respiratory sensitization
C = Ceiling Limit F = Fume	SS = Skin sensitization
	STEL = Short term Exposure limit values TD = Total dust
IPEL = Internal Permissible Exposure Limit OSHA = Occupational Safety and Health Administration.	TLV = Threshold Limit Value
John – Occupational Salety and reditit AuthiniStration.	

TWA

- OSHA = Occupational Safety and Health Administration.
 - = Respirable R

Ζ = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

Consult local authorities for acceptable exposure limits.

United States Page: 5/12

= Time Weighted Average

Product name Russet

Section 8. Exposure controls/personal protection

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection <u>Skin protection</u>	:	Safety glasses with side shields.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state: Solid.Color: Not available.Odor: Not available.Odor threshold: Not available.pH: Not available.pH: Not available.Boiling point: Not available.Boiling point: Not available.Flash point: Closed cup: Not applicable.Material supports: Metsavallable.Composition temperature: Not available.Plantin temperature: Not available.Poecomposition temperature: Not available.Lower and upper explosive: Not available.Evaporation rate: 0.1 (butyl acetate = 1)Vapor density: Not available.Relative density: 2.59Density (lbs / gal): 2.161Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Valative density: 3.4% (v/v), 10% (w/w)Visolut (uw): 90	<u>rippoururioo</u>		
OdoriNot available.Odor thresholdiNot available.pHiNot available.Melting pointiNot available.Boiling pointiNot available.Boiling pointiNot available.Flash pointiClosed cup: Not applicable.Material supportsiNot available.combustion.iNot available.Auto-ignition temperatureiNot available.Decomposition temperatureiNot available.Flammability (solid, gas)iNot available.Lower and upper explosive (flammable) limitsiLower: 1%Evaporation ratei0.1 (butyl acetate = 1)Vapor pressurei0.13 kPa (1 mm Hg) [room temperature]Vapor densityiNot available.Relative densityi2.59Density (Ibs / gal)i11.61SolubilityiInsoluble in the following materials: cold water.Partition coefficient: n- octanol/wateriNot available.Viscosityikinematic (40°C (104°F)): Not applicable.Volatilityi34% (v/v), 10% (w/w)	Physical state	1	Solid.
Odor threshold pH:Not available.pH:Not available.Melting point:Not available.Boiling point:Not available.Flash point:Closed cup: Not applicable.Material supports combustion.:Yes.Auto-ignition temperature flammability (solid, gas):Not available.Pecomposition temperature (fiammable) limits:Not available.Evaporation rate (flammability density):Not available.Vapor pressure (flammability (solid, gas):::::Vapor density Solubility::Solubility:::Solubility::Solubility::Solubility::	Color	1	Not available.
pH: Not available.Melting point: Not available.Boiling point: Not available.Flash point: Closed cup: Not applicable.Material supports combustion.: Ves.Auto-ignition temperature composition temperature: Not available.Pecomposition temperature (flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Lower: 1%Evaporation rate (flammable) limits: 0.1 (butyl acetate = 1)Vapor pressure (panting density): Not available.Pensity (lbs / gal): 2.59Density (lbs / gal): 2.161Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)	Odor	1	Not available.
Melting point:Not available.Boiling point:Not available.Flash point:Closed cup: Not applicable.Material supports:Ves.combustion.:Ves.Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Lower: 1%(flammable) limits:0.1 (butyl acetate = 1)Vapor pressure:0.1 (butyl acetate = 1)Vapor density:Not available.Relative density:2.59Density (lbs / gal):21.61Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): Not applicable.Volatility::34% (v/v), 10% (w/w)	Odor threshold	:	Not available.
Boiling point:Not available.Flash point:Closed cup: Not applicable.Material supports:Yes.Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Lower: 1%(flammable) limits:0.1 (butyl acetate = 1)Vapor pressure:0.13 kPa (1 mm Hg) [room temperature]Vapor density:Not available.Relative density:2.59Density (lbs / gal):21.61Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): Not applicable.Volatility:34% (v/v), 10% (w/w)	рН	4	Not available.
Flash point: Closed cup: Not applicable.Material supports: Mes.Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Evaporation rate: 0.1 (butyl acetate = 1)Vapor pressure: 0.1 (butyl acetate = 1)Vapor density: Not available.Relative density: 2.59Density (lbs / gal): 21.61Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)	Melting point	1	Not available.
Material supports combustion.Material supports es.Auto-ignition temperature Decomposition temperature Flammability (solid, gas)Not available.Decomposition temperature (flammable) limitsNot available.Evaporation rate (flammable) limits0.1 (butyl acetate = 1)Vapor pressure Vapor density0.13 kPa (1 mm Hg) [room temperature]Vapor density Relative density2.59Density (Ibs / gal)21.61SolubilityInsoluble in the following materials: cold water.Partition coefficient: n- octanol/waterKinematic (40°C (104°F)): Not applicable.Volatility34% (v/v), 10% (w/w)	Boiling point	1	Not available.
combustion.Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Lower: 1%(flammable) limits: Lower: 1%Evaporation rate: 0.1 (butyl acetate = 1)Vapor pressure: 0.13 kPa (1 mm Hg) [room temperature]Vapor density: Not available.Relative density: 2.59Density (lbs / gal): 21.61Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Kinematic (40°C (104°F)): Not applicable.Viscosity: 34% (v/v), 10% (w/w)	Flash point	1	Closed cup: Not applicable.
Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Lower: 1%(flammable) limits: Lower: 1%Evaporation rate: 0.1 (butyl acetate = 1)Vapor pressure: 0.13 kPa (1 mm Hg) [room temperature]Vapor density: Not available.Relative density: 2.59Density (lbs / gal): 21.61Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)		:	Yes.
Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Lower: 1%Evaporation rate: 0.1 (butyl acetate = 1)Vapor pressure: 0.13 kPa (1 mm Hg) [room temperature]Vapor density: Not available.Relative density: 2.59Density (lbs / gal): 21.61Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)	Auto-ignition temperature	1	Not available.
Lower and upper explosive (flammable) limits: Lower: 1%Evaporation rate (appr pressure (appr density): 0.1 (butyl acetate = 1)Vapor pressure (appr density): 0.13 kPa (1 mm Hg) [room temperature]Vapor density (appr density): 0.13 kPa (1 mm Hg) [room temperature]Vapor density (appr density): 2.59Density (lbs / gal) Solubility: 21.61Solubility (bactate): Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity (volatility): Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)	Decomposition temperature	1	Not available.
(flammable) limitsEvaporation rate: 0.1 (butyl acetate = 1)Vapor pressure: 0.13 kPa (1 mm Hg) [room temperature]Vapor density: 0.13 kPa (1 mm Hg) [room temperature]Vapor density: 0.13 kPa (1 mm Hg) [room temperature]Relative density: 2.59Density (lbs / gal): 21.61Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)	Flammability (solid, gas)	1	Not available.
Vapor pressure: 0.13 kPa (1 mm Hg) [room temperature]Vapor density: Not available.Relative density: 2.59Density (lbs / gal): 21.61Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)		;	Lower: 1%
Vapor density: Not available.Relative density: 2.59Density (lbs / gal): 21.61Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)	Evaporation rate	1	0.1 (butyl acetate = 1)
Relative density: 2.59Density (lbs / gal): 21.61Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)	Vapor pressure	1	0.13 kPa (1 mm Hg) [room temperature]
Density (lbs / gal): 21.61Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)	Vapor density	1	Not available.
Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)	Relative density	1	2.59
Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)	Density(lbs / gal)	1	21.61
octanol/waterViscosity: Kinematic (40°C (104°F)): Not applicable.Volatility: 34% (v/v), 10% (w/w)	Solubility	1	Insoluble in the following materials: cold water.
Viscosity : Kinematic (40°C (104°F)): Not applicable. Volatility : 34% (v/v), 10% (w/w)		1	Not available.
Volatility : 34% (v/v), 10% (w/w)			
	· · · · · · · · · · · · · · · · · · ·		
	% Solid. (w/w)	:	90

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Product name Russet

Section 10. Stability and reactivity

Hazardous decomposition products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result		Species	Dose	Exposure
diiron trioxide	LD50 Oral		Rat	10 g/kg	-
Conclusion/Summary	: There are	e no data a	vailable on the mixture its	elf.	L
rritation/Corrosion					
Conclusion/Summary					
Skin	: There are	e no data a	vailable on the mixture itse	elf.	
Eyes	: There are	e no data a	vailable on the mixture itse	elf.	
Respiratory	: There are	e no data a	vailable on the mixture itse	elf.	
Sensitization					
Conclusion/Summary					
Skin	: There are	e no data a	vailable on the mixture itse	elf.	
Respiratory	: There are	e no data a	vailable on the mixture itse	elf.	
<u>Autagenicity</u>					
Conclusion/Summary	: There are	e no data a	vailable on the mixture itse	elf.	
Carcinogenicity					
Conclusion/Summary	: There are	e no data a	vailable on the mixture itse	elf.	
Classification					
Product/ingredient name	OSHA	IARC	NTP		
		3			

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category
Russet	Category 3

Specific target organ toxicity (repeated exposure)

Not available.

United States Page: 8/12

Product name Russet

Section 11. Toxicological information

Τ	a	rq	et	or	Q	а	ns	

: Contains material which causes damage to the following organs: brain, central nervous system (CNS). Contains material which may cause damage to the following organs: lungs, upper

respiratory tract, skin, eyes.

Aspiration hazard

Name		Result
Naphtha (petroleum), heavy	alkylate	ASPIRATION HAZARD - Category 1
Information on the likely rou	tes of exposure	-
Potential acute health effec	<u>ts</u>	
Eye contact	: Exposure to airborne concentrations about may cause irritation of the eyes.	ove statutory or recommended exposure limits
Inhalation	: May cause respiratory irritation.	
Skin contact	: Defatting to the skin. May cause skin dr	yness and irritation.
Ingestion	: No known significant effects or critical h	azards.
Over-exposure signs/symp	<u>toms</u>	
Eye contact	: Adverse symptoms may include the follo irritation redness	owing:
Inhalation	: Adverse symptoms may include the follo respiratory tract irritation coughing	owing:
Skin contact	: Adverse symptoms may include the follo irritation dryness cracking	owing:
Ingestion	: No specific data.	
Delayed and immediate effect	cts and also chronic effects from short an	<u>id long term exposure</u>
Conclusion/Summary	 concentrations in excess of the stated of health effects such as mucous membrate effects on the kidneys, liver and central headache, dizziness, fatigue, muscular volume loss of consciousness. Solvents may can through the skin. There is some evident vapors in combination with constant loud expected from exposure to noise alone. of dust can produce eye irritation. Reperchange chronic respiratory irritation. Ingestion matches into account, where known, delayed and the state of the state o	ure itself. Exposure to component solvent vapor ccupational exposure limit may result in adverse ne and respiratory system irritation and adverse nervous system. Symptoms and signs include weakness, drowsiness and, in extreme cases, ause some of the above effects by absorption ce that repeated exposure to organic solvent d noise can cause greater hearing loss than Repeated exposure of the eyes to a low level eated or prolonged inhalation of dust may lead to nay cause nausea, diarrhea and vomiting. This ed and immediate effects and also chronic and long-term exposure by oral, inhalation and act.
<u>Short term exposure</u>		
Potential immediate effects	: There are no data available on the mixtu	ure itself.
Potential delayed effects Long term exposure	: There are no data available on the mixtu	ure itself.

Product name Russet

Section 11. Toxicological information

Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	<u>ects</u>
General	 Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Not available.	

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.		cleaned or rinsed out. Empty containers or liners may retain some product residues.
---	--	---

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Product name Russet

Section 13. Disposal considerations

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards Marine pollutant substances	No. Not applicable.	No. Not applicable.	No. Not applicable.

Additional information

DOT	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

÷

United States

United States inventory (TSCA 8b) : All components are listed or exempted.

U.S. Federal regulations

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification	:	Fire hazard	
		Immediate (acute) health hazard	

Composition/information on ingredients

Section 15. Regulatory information

Name	hazard	Sudden release of pressure	Reactive	(acute) health	Delayed (chronic) health hazard	
Naphtha (petroleum), heavy alkylate	Yes.	No.	No.	Yes.	No.	-

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

```
Hazardous Material Information System (U.S.A.)
```

```
Health : 2 Flammability : 0 Physical hazards : 0 (*) - Chronic effects
```

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Ass	ociation (U.S.A.)
Health : 2 Flamma	ability : 0 Instability : 0
Date of previous issue	: 11/14/2016
Organization that prepared the MSDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Indicates information that has changed from previously issued version.

<u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.