



## EasiSolv 120 Solvent Cleaner

### ***Product Description:***

EasiSolv™ 120 Solvent Cleaner is a quick drying cleaner formulated to effectively dissolve and remove printing inks from screen printing mesh, squeegees, flood bars, presses, pad printing tools, rotary screens and more. The combination of components is designed to solubilize and remove virtually every type of ink and minimize any remaining stains.

### ***Physical & Chemical Data:***

<b><i>Appearance &amp; Odor:</i></b>	Clear liquid with ether-like odor.
<b><i>Specific Gravity:</i></b>	0.95 @ 20 °C / 68 °F
<b><i>Vapor Pressure:</i></b>	3.6 mm Hg @ 20 °C / 68 °F
<b><i>Vapor Density:</i></b>	Heavier than air
<b><i>Boiling Point:</i></b>	> 140 °C / 284 °F
<b><i>pH:</i></b>	Neutral
<b><i>VOC:</i></b>	950 grams/liter
<b><i>Flash Point:</i></b>	118 °F / 48 °C

### ***Special features:***

- EasiSolv 120 effectively dissolves most inks, including: conventional/solvent, electronic, solder mask, UV, plastisol, water base and pad inks.
- EasiSolv 120 has a high flash point, yet will evaporate quickly and without leaving a residue which makes tape applications very simple and lasting.
- EasiSolv 120 is not SARA (Superfund Amendments Reauthorization Act) reportable which requires less solvent monitoring and paperwork.
- EasiSolv 120 may be applied manually or recirculated through the EasiFlo™ System, or in an enclosed, automatic screen washing system, providing superior product life and economy.

### ***Application:***

- Scrape all excess ink from screen.
- Apply EasiSolv 120 by squirt bottle, pneumatic sprayer or by rag to the (well) ink side of the screen.
- Thoroughly agitate ink with a rag or scrubber, then wipe up all dissolved ink.
- Reapply if necessary and follow with a dry rag, wipe on both sides of the screen.
- The screen will be ready for printing or tape application within 20 seconds.