Sportsman® EX



Automatic Screen Printing Press



M&R's Sportsman EX presses are the benchmark in midrange automatic screen printing presses, combining quality components, leading class craftsmanship and high speed production to give you one of the finest presses, at an amazingly affordable price.

Featuring electric printheads and time-saving features like tool-free squeegee/floodbar angle adjustments with air locks and pneumatic frame locks, the Sportsman EX is designed to maximize your run times while minimizing setup times.

With three different model sizes and in 6-, 8-, 10- and 12-color configurations, there is sure to be a Sportsman EX that meets your needs. You can rest assured that whichever you choose, M&R has you covered with best-in-class design, service and support.

FEATURES

- Available in 6-, 8-, 10- and 12-color models
- Maximum image area: 41 x 46 cm (16" x 18"),
 51 x 51 cm (20" x 20") or 51 x 71 cm (20" x 28")
- Standard pallet size: 41 x 56 cm (16" x 22"),
 56 x 63 cm (22" x 25") or 56 x 76 cm (22" x 30")
- Standard front and rear micro-registration
- Standard pneumatic squeegee/floodbar and frame locks
- High-resolution touchscreen control panel with easy-to-use, icon-based logic and built-in tutorial screens

Find more information and where to buy at: www.mrprint.com



Sportsman® EX

Operate Faster Than Ever!

The Sportsman EX features a 7.5" high-resolution touchscreen interface with easy-to-learn logic and

enhanced icon graphics.

Built-in tutorial screens give quick onscreen access to multi-language setup guides. The operating instructions effectively put a user's manual at the operator's fingertips.

The intuitive icon-based interface is identical on both M&R's Sportsman EX and Diamondback E™ presses, making it easy for operators to run either press with minimal training.

Requirements

Shipping Weight

Standard Pallet Size





	Sportsman EX 4045 8/6	Sportsman EX 4045 10/8	Sportsman EX 4045 12/10	Sportsman EX 4045 14/12	Sportsman EX 5050 8/6	Sportsman EX 5050 10/8
Air @ 6,9 bar (100 psi)	198 I/min (7 cfm)	255 I/min (9 cfm)	255 l/min (9 cfm)	368 I/min (13 cfm)	198 I/min (7 cfm)	255 I/min (9 cfm)
Diameter	358 cm (11' 9")	386 cm (12' 8")	422 cm (13' 10")	464 cm (15' 2")	386 cm (12' 8")	424 cm (13' 11")
Electrical	208/230 V, 1 ph, 31 A, 50/60 Hz, 3.3 kW	208/230 V, 1 ph, 38 A, 50/60 Hz, 3.9 kW	208/230 V, 1 ph, 43 A, 50/60 Hz, 4.6 kW	208/230 V, 1 ph, 46 A, 50/60 Hz, 5.32 kW	208/230 V, 1 ph, 31 A, 50/60 Hz, 3.3 kW	208/230 V, 1 ph, 38 A, 50/60 Hz, 3.9 kW
Requirements ¹	208/230 V, 3 ph, 20 A, 50/60 Hz, 3.3 kW	208/230 V, 3 ph, 22 A, 50/60 Hz, 3.9 kW	208/230 V, 3 ph, 28 A, 50/60 Hz, 4.6 kW	208/230 V, 3 ph, 30 A, 50/60 Hz, 5.32 kW	208/230 V, 3 ph, 20 A, 50/60 Hz, 3.3 kW	208/230 V, 3 ph, 22 A, 50/60 Hz, 3.9 kW
	380/415 V, 3 ph, 10 A, 50/60 Hz, 3.3 kW	380/415 V, 3 ph, 11 A, 50/60 Hz, 3.9 kW	380/415 V, 3 ph, 14 A, 50/60 Hz, 4.6 kW	380/415 V, 3 ph, 17 A, 50/60 Hz, 5.32 kW	380/415 V, 3 ph, 10 A, 50/60 Hz, 3.3 kW	380/415 V, 3 ph, 11 A, 50/60 Hz, 3.9 kW
Maximum Frame Size	58 x 84 x 5 cm (23" x 33" x 2")	58 x 84 x 5 cm (23" x 33" x 2")	58 x 84 x 5 cm (23" x 33" x 2")	58 x 84 x 5 cm (23" x 33" x 2")	66 x 91 x 5 cm (26" x 36" x 2")	66 x 91 x 5 cm (26" x 36" x 2")
Maximum Image Area	41 x 46 cm (16" x 18")	51 x 51 cm (20" x 20")	51 x 51 cm (20" x 20")			
Shipping Weight	1497 kg (3300 lb)	1819 kg (4010 lb)	2037 kg (4490 lb)	2494 kg (5500 lb)	1724 kg (3800 lb)	2087 kg (4600 lb)
Standard Pallet Size	41 x 56 cm (16" x 22")	41 x 56 cm (16" x 22")	41 x 56 cm (16" x 22")			
					56 x 63 cm (22" x 25")	56 x 63 cm (22" x 25")
	Sportsman EX 5050 12/10	Sportsman EX 5050 14/12	Sportsman EX 5070 8/6	Sportsman EX 5070 10/8	Sportsman EX 5070 12/10	Sportsman EX 5070 14/12
Air @ 6,9 bar (100 psi)	255 I/min (9 cfm)	368 I/min (13 cfm)	227 I/m (8 cfm)	227 I/m (8 cfm)	326 l/m (11.5 cfm)	326 l/m (11.5 cfm)
Diameter	471 cm (15' 5")	518 cm (17')	411 cm (13' 6")	461 cm (15' 2")	503 cm (16' 6")	551 cm (18' 1")
Electrical	208/230 V, 1 ph, 43 A, 50/60 Hz, 4.6 kW	208/230 V, 1 ph, 46 A, 50/60 Hz, 6 kW	208/230 V, 1 ph, 31 A, 50/60 Hz, 3.3 kW	208/230 V, 1 ph, 38 A, 50/60 Hz, 3.9 kW	208/230 V, 1 ph, 43 A, 50/60 Hz, 4.6 kW	208/230 V, 1 ph, 47 A, 50/60 Hz, 6 kW

208/230 V, 3 ph, 20 A, 50/60 Hz, 3.3 kW | 208/230 V, 3 ph, 22 A, 50/60 Hz, 3.9 kW | 208/230 V, 3 ph, 28 A, 50/60 Hz, 4.6 kW | 208/230 V, 3 ph, 32 A, 50/60 Hz, 6 kW

380/415 V, 3 ph, 14 A, 50/60 Hz, 4.6 kW

66 x 109 x 5 cm (26" x 43" x 2")

51 x 71 cm (20" x 28")

56 x 76 cm (22" x 30")

2722 kg (6000 lb)

380/415 V, 3 ph, 17 A, 50/60 Hz, 6 kW

66 x 109 x 5 cm (26" x 43" x 2")

51 x 71 cm (20" x 28")

56 x 76 cm (22" x 30")

3311 kg (7300 lb)

380/415 V, 3 ph, 11 A, 50/60 Hz, 3.9 kW

66 x 109 x 5 cm (26" x 43" x 2")

51 x 71 cm (20" x 28")

56 x 76 cm (22" x 30")

1814 kg (4000 lb)

1 If incoming voltage differs from the voltage(s) listed in this brochure, calculate amperage accordingly. Other electrical configurations are available: Contact The M&R Companies for details.

208/230 V, 3 ph, 28 A, 50/60 Hz, 4.6 kW 208/230 V, 3 ph, 30 A, 50/60 Hz, 6 kW

380/415 V, 3 ph, 17 A, 50/60 Hz, 6 kW

66 x 91 x 5 cm (26" x 36" x 2")

51 x 51 cm (20" x 20")

41 x 56 cm (16" x 22")

56 x 63 cm (22" x 25")

3039 kg (6700 lb)

380/415 V, 3 ph, 14 A, 50/60 Hz, 4.6 kW

Maximum Frame Size 66 x 91 x 5 cm (26" x 36" x 2")

2404 kg (5300 lb)

41 x 56 cm (16" x 22")

56 x 63 cm (22" x 25")

Maximum Image Area 51 x 51 cm (20" x 20")

380/415 V, 3 ph, 10 A, 50/60 Hz, 3.3 kW

66 x 109 x 5 cm (26" x 43" x 2")

51 x 71 cm (20" x 28")

56 x 76 cm (22" x 30")

1633 kg (3600 lb)