

Street Fighter Colors™

The Street Fighter Colors™ provide saturated standard colors in a great value optic lens module for standard and lower-profile channel letters.



SPECIFICATIONS

| | |
|-------------------|---|
| Beam Angle | 160° Low Dome, Batwing Optic |
| Certifications | UL & cUL Recognized (SAM Manual), CE, RoHs |
| Dimensions | 0.7"W x 3.55"L x 0.35"H |
| Fastening | Peel & stick / Mechanical screw hole |
| Input | 12VDC |
| Intensity | See Product Options |
| Max Mods (Series) | 45 mods (25 ft.) |
| Operating Temp | -40° to +60°C |
| Packaging | 90 mods (50 ft.) per bag or 1,080 mods (600 ft.) per case |
| Power Supply | P-LED 12VDC |
| Protection Grade | IP67 |
| Spacing | 1.8 mods/ft. (fully stretched) |
| Warranty | 10-Year Product / 5-Year Limited Labor |

FEATURES

- For use in channel letters
- Wide module spacing reduces module count and installation time
- Great in areas with indirect water exposure or salt spray
- Split wires for easy module adjustment and splicing
- VHB tape coupled with a mechanical screw hole mounting option

WIRING DETAILS

| | |
|-------------|----------|
| White/Black | Negative |
| Red | Positive |
| Green | Positive |
| Blue | Positive |
| Orange | Positive |

PRODUCT OPTIONS

| Color | Wavelength | Efficacy | Intensity | Power | Run Footage | UL Part Number | Ordering Part Number |
|--------|------------|----------|-------------------------|----------------------|-------------------------|-----------------|----------------------|
| Red | 625nm | 20 LM/W | 13 LM/mod (23.4 LM/ft.) | 0.65W/mod (1.2W/ft.) | 90 mods (50 ft.)/60W PS | PL-OP2-SC3-P-RD | M-SFCX3-RD |
| Green | 525nm | 52 LM/W | 34 LM/mod (61.2 LM/ft.) | 0.65W/mod (1.2W/ft.) | 90 mods (50 ft.)/60W PS | PL-OP2-SC3-P-GR | M-SFCX3-GR |
| Blue | 460nm | 18 LM/W | 12 LM/mod (21.6 LM/ft.) | 0.65W/mod (1.2W/ft.) | 90 mods (50 ft.)/60W PS | PL-OP2-SC3-P-BL | M-SFCX3-BL |
| Orange | 609nm | 34 LM/W | 22 LM/mod (39.6 LM/ft.) | 0.65W/mod (1.2W/ft.) | 90 mods (50 ft.)/60W PS | PL-OP2-SC3-P-OR | M-SFCX3-OR |

RECOMMENDED COVERAGE CHART

| Depth | Max. Stroke | Row Spacing |
|-------|-------------|-----------------|
| | Single Row | Multi-Rows O.C. |
| 4" | 9" | 5" |
| 5" | 12" | 10" |
| 6" | 14" | 12" |
| 7" | 14" | 12" |

Note: Product and depth may vary depending on face material and desired brightness.

