

Street Fighter Mini Colors™

The Street Fighter Mini™ Colors is great for narrow letters with thin strokes – now in various popular color choices!



SPECIFICATIONS

Beam Angle	120° High Dome, Lambertian
Certifications	UL & cUL Recognized (SAM Manual), CE, RoHs
Dimensions	0.3"W x 1.2"L x 0.17"H
Fastening	Peel & stick, silicone required (Peel and stick for temporary placement only)
Input	12VDC
Max Mods (Series)	45 mods (10 ft.)
Operating Temp	-40° to +60°C
Packaging	180 mods (40 ft.) per bag or 7,200 mods (1,600 ft.) per case
Power Supply	P-LED 12VDC
Protection Grade	IP67
Run Footage	See Product Options
Spacing	4.5 mods/ft. (fully stretched)
Warranty	10-Year Product / 5-Year Limited Labor

FEATURES

- Perfect for small channel letters
- Great in areas with indirect water exposure or salt spray
- Split wires for easy module adjustment and splicing
- LM-79/LM-80 third party tested
- VHB tape coupled with a mechanical screw-hole mounting option

WIRING DETAILS

White/Red	Positive
White	Negative

PRODUCT OPTIONS

Product	Wavelength	Efficacy	Intensity	Power	Run Footage	UL Part Number	Ordering Part Numbers
RED	625nm	19 LM/W	6 LM/mod (27 LM/ft.)	0.32W/mod (1.44W/ft.)	180 mods (40 ft.)/60W PS	PL-OP5-SC2-P-RD	M-SFMC2-RD
GREEN	525nm	46 LM/W	11 LM/mod (49.5 LM/ft.)	0.24W/mod (1.08W/ft.)	180 mods (40 ft.)/60W PS	PL-OP5-SC2-P-GR	M-SFMC2-GR
BLUE	460nm	13 LM/W	3 LM/mod (13.5 LM/ft.)	0.24W/mod (1.08W/ft.)	180 mods (40 ft.)/60W PS	PL-OP5-SC2-P-BL	M-SFMC2-BL

RECOMMENDED COVERAGE CHART

Depth	Max. Stroke	Row Spacing
	Single Row	Multi-Rows O.C.
2"	3"	2.5"
3"	5"	5"
4"	6"	6"
5"	8"	6"

Note: Product and depth may vary depending on face material and desired brightness.

